



STRIPP IP54

OUTDOOR

Fix (not adjustable) 0° - 0°

□ 3.27" × 9.80"

Material : waterproof CALCYT+®



STRIPP LED DIM 100 LM

REF N° 144 60 505 CRI 80 warm white 2200°K

REF N° 144 60 005 CRI 90 warm white 2700°K

REF N° 144 60 105 CRI 90 warm white 3000°K

REF N° 144 60 205 CRI 90 neutral white 4000°K

REF N° 144 60 305 royal blue

1W - excl. LED driver -

current controlled 350mA -

Ⓟ - serial wiring - 3 Step MacAdam

Requires remote LED driver - 350mA

STRIPP LED DIM 200 LM

REF N° 144 62 505 CRI 80 warm white 2200°K

REF N° 144 62 005 CRI 90 warm white 2700°K

REF N° 144 62 105 CRI 90 warm white 3000°K

REF N° 144 62 205 CRI 90 neutral white 4000°K

REF N° 144 62 305 royal blue

2W - excl. LED driver -

current controlled 350mA -

Ⓟ - serial wiring - 3 Step MacAdam

Requires remote LED driver - 350mA

STRIPP LED DIM 400 LM

REF N° 144 61 505 CRI 80 warm white 2200°K

REF N° 144 61 005 CRI 90 warm white 2700°K

REF N° 144 61 105 CRI 90 warm white 3000°K

REF N° 144 61 205 CRI 90 neutral white 4000°K

REF N° 144 61 305 royal blue

4W - excl. LED driver -

current controlled 350mA -

Ⓟ - serial wiring - 3 Step MacAdam


Requires remote LED driver - 350mA

Ready for installation in solid walls
Optional plasterkit for installation into gypsum walls

PLASTERKIT STRIPP

REF N° 744 01 000 For mounting into gypsum walls

Housing: perforated aluminum



STRIPP

designplan™

79 Trenton Avenue
Frenchtown, NJ 08825

Tel: (908) 996-7710
Fax: (908) 996-7042