

Technical features

IP 65 IK 09

Technical data


Wattage	14W
IP Rating	IP65
IK Rating	IK09
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	NR. 5 CREE "XP-L" LED down.
Screws	Stainless steel
Transformer	Electronic power supply 120VAC 50-60Hz built-in
Gasket	Silicone rubber
Rubber grommet	M20 Rutaseal® in EPDM
Glass	Tempered
Gross weight	6.6 lbs






401019P

TECH MEDIUM 01 SQUARE PRO

Square wall mounted luminaire for outdoor installation on a facade/wall, with light distribution downward only. Phospho-chromatized and polyester powder coated die-cast copper-free aluminum body, tempered safety glass, molded silicone gasket and stainless steel screws. Built-in LED driver 120VAC 50-60Hz, with 5 CREE XP-L LED. IP65 rating.



light source*	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
3000°K warm-white			
high-power led	 10°	1,300	92.86
high-power led	 30°	1,230	87.86
high-power led	 45°	1,170	83.57

* Other light colors available on request: Neutral-white

Finish color options:

-  Textured Gray RAL 9006
-  Anthracite Gray RAL 7016
-  Matte Black (on request)

