




401102RGBWP

Surface mounted luminaire for outdoor installation on window sill, with asymmetric 8°x170° “window-washer” light distribution. Phospho-chromatised and polyester powder coated die-cast copper-free aluminum body, polycarbonate diffuser, molded silicone gasket and stainless steel screws. Remote 24VDC power supply needed, DMX driver integrated; with 1 x CREE “XML” RGBW LED. IP65 rating.



Technical features

- IP65
 - IK08
 - DMX
- NEW**

Technical data

Wattage	4.5 WATT
IP Rating	IP65
IK Rating	IK08
Material	High corrosion resistance die-cast copper-free aluminum body
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x CREE “XML” COLOR RGBW LED
Screws	Stainless steel
DMX	DMX interface integrated
Remote driver	Constant voltage 24VDC remote driver needed
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	2.20 lbs

light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
RGBW			
high-power led	8° x 170°12°	160	35.55

Finish color options:

- Textured Grey
RAL 9006
- Anthracite Grey
RAL 7016
- Matte Black
(on request)



DMX ACCESSORIES **CONTROLLERS, SPLITTERS, ETC...**

To be defined together with puk technical department, according to project specifications and after providing installation details.