



datasheet

Top is an elegant indoor pendant, offered in 2 sizes, that is both geometric and organic at the same time. Each fixture is made from a single block of solid acrylic and emits a glowing effect that will warm any residence or workplace. Available in 3000K and 3 standard finishes.

TECHNICAL DATA

Wattage / Input	12W (120VAC)
Power Supply	Integral
Dimming	0-10V Dimming
Construction	Body: Aluminum, Brass Lens: Acrylic
ССТ	3000K
CRI	>90
Delivered Lumens	1200 lm (9W version)
	1750 lm (12W version)
Efficacy	133.3 lm/W (9W version)
	145.8 lm/W (12W version)
Optics	Diffuse
Finishes	Black, White, Brass
Fixture Dimensions	Ø7.9" x 7.1" h (9W version)
	Ø12.6" x 11.8" h (12W version)
Fixture Weight	_
IP Rating	IP20



Fixture Dimensions

80.2

97.87"

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2

00.2


00

ORDERING INFORMATION

Example: N8323N.

Model No.	Description
N8320	Ø7.9" - 12W - 3000K - Black
N8321	Ø7.9" - 12W - 3000K - White
N8322	Ø7.9" - 12W - 3000K - Brass
N8323	Ø12.6" - 12W - 3000K - Black
N8324	Ø12.6" - 12W - 3000K - White
N8325	Ø12.6" - 12W - 3000K - Brass

PHOTOMETRIC DATA



Fixture Type Designation:

Job Name/Date:

P: 908-996-7710 F: 908-996-7042