

datasheet


W200-CR is a Ø3.0" round, recessed LED wall light suitable for indoor installation with Tru-Colour® 97 CRI and a 7 year warranty. It is available in 2 standard finishes with a 90° beam angle and 75° gimbal angle.

#### **TECHNICAL DATA**


Wattage / Input	5W (400mA)		
Power Supply	Remote, not included. See page 2.		
Construction	Body: Cable Length: AC - 4.92', DC 0.98'		
ССТ	3000K		
CRI	98 (Tru-Colour <sub>®</sub> )		
Delivered Lumens	200 lm (3000K)		
Efficacy	40 lm/W (3000K)		
Optics	90° Beam Angle 75° Gimbal Angle		
Finishes	Silver, White		
Lumen Maintenance	70,000 hrs L70, B10 (Ta 25°C)		
Operating Temp.	-22 to 185°F		
Color Consistency	0-Step MacAdam		
Fixture Dimensions	Ø3.0"		
Fixture Weight	0.71 lbs		
Gimbal Angle	N/A		
IP Rating	IP43		
Warranty	7 years		

Tru-Colour® lights score a 98 on the color rendering index (CRI) which is the top rating for high CRI LEDs. Tru-Colour LEDs contain about a billion colours, which is more than any other white LED on the market. All these colors in one small LED means that you see colors as they really are. Tru-Colour has TM-30 color fidelity and the purest red on the market - Rf CES07 (R9 on the old CRI scale).





#### **Fixture Dimensions**





## **ORDERING INFORMATION**

Example: W200-CR-3K-90.75-S.US. Accessories / Power Supplies ordered separately.

W200	- CR	- 3K	- 90.75	- LUS
Model No.		ССТ	Optics	Finish
W200	CR - Curve	<b>3K</b> - 3000K	<b>90.75</b> - 90° / 75°	S - Silver .US W - White

Job Name/Date: Fixture Type Designation:

© Copyright 2022 Designplan Lighting, Inc. Published: December 7, 2022

P: 908-996-7710 F: 908-996-7042

1 of 2





datasheet

# SUGGESTED POWER SUPPLIES


400mA


Part Number	Description	Input/Output	# of Fixtures
PPLT00466-P	0-10V Dimming to 1.0%	120-277VAC to 400mA, 10W, Class 2, DAMP	1-2
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 400mA, 20W, Class 2, DAMP	1-4
PPLT00309-P	0-10V Dimming to 0.1%	120-277VAC to 400mA, 50W, Class 2, DAMP	1-6
PPLT00538-P	0-10V Dimming to 0.1% (4 channels)	120-277VAC to 400mA, 100W, Class 2	1-5 (1-20)

For other power supply options consult factory.

### PHOTOMETRIC DATA

Note all Photometry is 3000K





PHOTOMETRIC FILENAME : W200-CR-90-75 IES.IES

Launched in 2008, Melbourne-based Brightgreen is a purpose-led B corporation that designs world-leading luminaires with patented Tru-Colour® technology. As a certified B Corp, Brightgreen meets the highest standards for social and environmental performance, transparency, and accountability—using its business for the greater good.

www.bcorporation.net/en-us/find-a-b-corp/company/brightgreen

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710