

duvali

design by Landa R&D

EDEN OF LIGHT.



duvali

Duvali, the lighting device for paths with a power of 1.5/2.5W (Duvali_mini) and 8W (Duvali) has an evocative and elegant shape. A bollard made in Accoya® timber available with a height of 13.8", 23.6", 35.4" and 47.2". Duvali is absolute three-dimensionality, solidity and perfect light distribution. No design limit and maximum possible resistance, thanks to the technical solutions adopted.



duvali_mini



BOLLARD



Wattage 1.5W

Voltage 24VDC

Beam 





TECHNICAL SPECIFICATIONS

Source lamp	<u>LED 1.5W</u>
Total wattage	<u>1.5W</u>
Voltage	<u>24VDC</u>
Control	<u>On/Off</u>
Light color	<u>3000K • other colors on request</u>
Luminous flux (*Source flux)	<u>65 lm (137 lm*)</u>
Luminous efficacy	<u>44 lm/W</u>
McADAM steps	<u>3</u>
Beam	<u>Diffuse</u>
CRI	<u>> 90</u>
Life time	<u>L70 > 50.000 h Ta 40°C</u>
IP rating	<u>IP65</u>
IK rating	<u>IK08</u>

DIFFUSE 1.5W

Source lamp	<u>LED 1.5W</u>
Total wattage	<u>1.5W</u>
Voltage	<u>24VDC</u>
Control	<u>On/Off</u>
Light color	<u>3000K • other colors on request</u>
Luminous flux (*Source flux)	<u>65 lm (137 lm*)</u>
Luminous efficacy	<u>44 lm/W</u>
McADAM steps	<u>3</u>
Beam	<u>Diffuse</u>
CRI	<u>> 90</u>
Life time	<u>L70 > 50.000 h Ta 40°C</u>
IP rating	<u>IP65</u>
IK rating	<u>IK08</u>



MATERIALS

Body	<u>Accoya® wood and inox AISI 316L</u>
Diffuser	<u>Opal polycarbonate</u>
Finishing	<u>Acetylation treatment</u>

ORDER CODE

DV 4 0 035 D H B _ _ 3
 Voltage 7Z 24VDC

Example DV 4 0 035 D H B 7Z 3

INCLUDED ACCESSORIES

Code	Description
-	<u>Single connection IP68</u>
-	<u>Root mounting kit</u>

duvali



BOLLARD



Wattage 8W

Voltage Remote 350mA

Beam 





TECHNICAL SPECIFICATIONS

Source lamp	LED 5.5W
Total wattage	8W
Voltage	350mA, 50-60 Hz
Control	On/Off
Light color	3000K • other colors on request
Luminous flux (*Source flux)	542 lm (759 lm*)
Luminous efficacy	68 lm/W
McADAM steps	3
Beam	Diffuse
CRI	> 90
Life time	L70 > 50.000 h Ta 40°C
IP rating	IP65
IK rating	IK08

DIFFUSE

LED 5.5W
8W
350mA, 50-60 Hz
On/Off
3000K • other colors on request
542 lm (759 lm*)
68 lm/W
3
Diffuse
> 90
L70 > 50.000 h Ta 40°C
IP65
IK08



MATERIALS

Body	Accoya® wood and inox AISI 316L
Diffuser	Opal polycarbonate
Finishing	Acetylation treatment

ORDER CODE

DV 6 0	DHBBZ3		
	Height	060	23.62"
		090	35.43"
		120	47.24"

Example DV 6 0 060 DHBBZ3

INCLUDED ACCESSORIES

Code	Description
-	Single connection IP68
-	Root mounting kit

