

zygo
design by Landa R&D

A URBAN & BUCOLIC DREAM.

[UN SOGNO URBANO E BUCOLICO.]



zygo

All the traditional look in the shape and the most complete and advanced proposal of materials and technical-lighting technology in Zygo: the classic transported into modernity for a bollard available with a height of 23.6". A diffused light emission together with a power of 8W make this device ideal for lighting paths, access roads and gardens.



BOLLARD



Wattage8W

VoltageRemote 500mA

Beam

TECHNICAL SPECIFICATIONS

Source lamp	LED 5.5W
Total wattage	8W
Voltage	500mA, 50-60 Hz
Control	On/Off
Light color	3000K • other colors on request
Luminous flux>(*Source flux)	542 lm (759 lm*)
Luminous efficacy	68 lm/W
McADAM steps	3
Beam	Diffuse
CRI	> 90
Lifetime	L70 > 50.000 h Ta 40°C
IP rating	IP65
IK rating	IK08

DIFFUSE

LED 5.5W

8W

500mA, 50-60 Hz

On/Off

3000K • other colors on request

542 lm (759 lm*)

68 lm/W

3

Diffuse

> 90

L70 > 50.000 h Ta 40°C

IP65

IK08

MATERIALS

Body	Accoya® wood and inox AISI 316L
Diffuser	Opal polycarbonate
Finishing	Acetylation treatment

ORDER CODE

ZY 5 0 060 D H B 10 3

INCLUDED ACCESSORIES

Code	Description
-	Single connection IP68
-	Root mounting kit

2.4"

23.6"
3.7"



