

ELEMENT SLIM 1 / 1-B


Element Slim is a linear, wall-mounted luminaire with single or double emission versions. It is available in 4 different lengths, 3 color temperatures and an 89° or wall washer light beam. Element Slim 1 (mono) and 1-B (bi) are 4.9" in length with 3 color temperatures, and 5 standard finishes.



TECHNICAL DATA

Wattage / Input	2W - Element Slim 1 Mono 4W - Element Slim 1-B Bi
Power Supply	Remote, not included. Consult Factory.
Construction	Body: Anticorodal Aluminum (Anodized) Lens: Extra Clear, Screen-printed, Tempered Glass Cable Length: 1.64'
CCT	2700K, 3000K, 4000K
BUG Rating	B0-U1-G0 (3000K)
Delivered Lumens	210 lm (3000K - Mono - Element Slim 1) 420 lm (3000K - Bi - Element Slim 1-B)
Efficacy	105 lm/W (3000K)
Optics	2 Standard, See Below
Finishes	5 Standard, See Below
Fixture Dimensions	4.92" l x 3.94" w x 1.57" h
Color Consistency	<3-Step MacAdam
IP Rating	IP66
Impact Resistance	IK09

Fixture Dimensions



ORDERING INFORMATION

Example: LM02.104243.US.03.FL.BP Power Supplies ordered separately.

Model No.	Finish	Optic	CCT
LM02.104242.US - Element Slim 1 (Mono)	01 - White	FL - 89° Beam	BC - 2700K
LM02.104243.US - Element Slim 1-B (Bi)	02 - Black	WW - Wall Washer	BP - 3000K
	03 - Gray		BF - 4000K
	04 - Cor-ten		
	11 - Anthracite		
NOTE: Mono Emission can be Up or Down Bi Emission is Up and Down			

Job Name/Date:

Fixture Type Designation:


SUGGESTED POWER SUPPLIES

Consult Factory

PHOTOMETRIC DATA


Note: All photometric data is 3000K

Maximum Candela = 83.3



PHOTOMETRIC FILENAME : 02.104242.XX.FL.BP - LAM32 - ELEMENT SLIM 1 - MONO EMISSION - 3000K.IES

Maximum Candela = 186.9



PHOTOMETRIC FILENAME : 02.104242.XX.WW.BP - LAM32 - ELEMENT SLIM 1 - MONO EMISSION - 3000K.IES

Job Name/Date:

Fixture Type Designation: