

# ALTOPIANO 1.2


Altopiano is a family of compact, recessed outdoor downlights available in 3 sizes, round or square, suitable for hospitality and residential sectors, as well as steam rooms, NOT saunas. Available in static white, RGBW mixing or Dim to Warm. Altopiano 1.2 is the 3.9" round, RGBW version. PWM controller by others.



## TECHNICAL DATA

|                           |   |
|---------------------------|---|
| <b>Wattage / Input</b>    | 8W (24VDC)  |
| <b>Power Supply</b>       | Remote, not included. Consult factory.  |
| <b>Construction</b>       | Body: Thermally Conductive Technopolymer<br>Trim: Stainless Steel<br>Lens: Diffuse or Extra-clear Glass<br>Cable Length: 1.64' standard |
| <b>Ceiling Thickness</b>  | Works with ceilings 1/8" to 3/4" thick<br>For ceilings 3/64" to 1 3/8" thick, use spring clips  |
| <b>CCT</b>                | RGBW  |
| <b>CRI</b>                | —   |
| <b>Delivered Lumens</b>   | 310 lm: (R) 48 lm, (G) 117 lm, (B) 16 lm,<br>(W) 129 lm (3000K, 24°)  |
| <b>Efficacy</b>           | 38.8 lm/W (3000K, 24°)  |
| <b>Optics</b>             | 6 Standard (see below)  |
| <b>Finishes</b>           | 5 Standard, Custom RAL on request<br>(4 Stage Marine Grade Finish)  |
| <b>Fixture Dimensions</b> | Ø3.86" x 3.54" h  |
| <b>Cut-out Size</b>       | Ø3.54"  |
| <b>Fixture Weight</b>     | 1.32 lbs  |
| <b>LED Source</b>         | 1 High Intensity Power LED  |
| <b>Lumen Maintenance</b>  | 60,000 hrs L90, B10 (Ta 25°C)   |
| <b>Operating Temp.</b>    | -4°F to +113°F  |
| <b>IP Rating</b>          | IP66  |
| <b>IK Rating</b>          | IK08  |

Fixture Dimensions



## ORDERING INFORMATION

Example: AP1200000170LF. Accessories / Power Supplies ordered separately.

| AP1200  | 00                                 |  | 7        |  |   |
|---------|------------------------------------|--|----------|--|---|
| Model # | Control System                     | Accessories  | CCT      | Optics   | Finish  |
| AP1200  | 00 - PWM<br>(Controller by others) | 00 - None<br>01 - Honeycomb<br><i>Honeycomb Louvre not available on 0D (Diffuse) or 0W (23°x64°)</i> | 7 - RGBW | 0S - 14°<br>0M - 24°<br>0L - 37°<br>0K - 44°<br>0W - 14° x 63°<br>0D - Diffuse | H - Anthracite<br>T - Cor-ten<br>F - Gray<br>E - White<br>7 - Primer<br>C - Custom RAL<br>(consult factory for "C") |

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES


24VDC

| Part Number               | Description | Input/Output                      | # of Fixtures |
|---------------------------|-------------|-----------------------------------|---------------|
| <a href="#">PPLT00586</a> | Non-Dim     | 120-277VAC to 24VDC, 40W, Class 2 | 1-4           |
| <a href="#">PPLT00158</a> | Non-Dim     | 120VAC to 24VDC, 100W, Class 2    | 1-10          |

For other power supply options consult factory.

## ACCESSORIES

### Installation



### WCA19

Outer Casing

For solid ceilings (concrete)

Consult factory for regular ceilings



### WGA02


Retaining Spring Clip

Use for ceilings 3/64"

min. to 1 3/8" max. thick

## ACCESSORIES

### Anti-Glare



### Honeycomb Louvre

Built into the fixture  
The honeycomb louvre can be provided on all fixed optics except for diffuse and elliptical optics

## Various



### WNAP10A0

Anti-Fall Kit

## ACCESSORIES

### Controllers (RGBW)



### PPWD00570 - RGBW DMX512+Wifi Controller

Touch Sensitive

Can be controlled by WiFi

Controls 3 zones synchronously and separately

## PHOTOMETRIC DATA

See IES Files

Job Name/Date:

Fixture Type Designation: