

ALTOPIANO 1.3


Altopiano is a family of compact, recessed outdoor downlights available in 3 sizes, round or square, suitable for hospitality and residential sectors, as well as steam rooms, NOT saunas. Available in static white, RGBW mixing or Dim to Warm. Altopiano 1.3 is the 3.9" square, RGBW version. PWM controller by others.

TECHNICAL DATA

| | |
|---------------------------|---|
| Wattage / Input | 8W (24VDC) |
| Power Supply | Remote, not included. Consult factory. |
| Construction | Body: Thermally Conductive Technopolymer Trim: Stainless Steel Lens: Diffuse or Extra-clear Glass Cable Length: 1.64' standard |
| Ceiling Thickness | Works with ceilings 1/8" to 1" thick. For ceilings 3/64" to 5/64" thick, use spring clips. |
| CCT | RGBW |
| CRI | — |
| Delivered Lumens | 310 lm: (R) 48 lm, (G) 117 lm, (B) 16 lm, (W) 129 lm (3000K, 24°) |
| Efficacy | 38.8 lm/W (3000K, 24°) |
| Optics | 6 Standard (see below) |
| Finishes | 5 Standard, Custom RAL on request (4 Stage Marine Grade Finish) |
| Fixture Dimensions | 3.86" x 3.86" x 3.54" h |
| Cut-out Size | 3.54" x 3.54" |
| Fixture Weight | 1.32 lbs |
| LED Source | 1 High Intensity Power LED |
| Lumen Maintenance | 60,000 hrs L90, B10 (Ta 25°C) |
| Operating Temp. | -4°F to +113°F |
| IP Rating | IP66 |
| IK Rating | IK07 |



Fixture Dimensions



ORDERING INFORMATION

Example: AP1300100150KF. Accessories / Power Supplies ordered separately.

| AP1300 | 00 | | 7 | | |
|---------|------------------------------------|--|----------|--|---|
| Model # | Control System | Accessories | CCT | Optics | Finish |
| AP1300 | 00 - PWM (Controller by others) | 00 - None 01 - Honeycomb <i>Honeycomb Louvre not available on 0D (Diffuse) or 0W (23°x64°)</i> | 7 - RGBW | 0S - 14° 0M - 24° 0L - 37° 0K - 44° 0W - 14° x 63° 0D - Diffuse | H - Anthracite T - Cor-ten F - Gray E - White 7 - Primer C - Custom RAL (consult factory for "C") |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES


24VDC

| Part Number | Description | Input/Output | # of Fixtures |
|---------------------------|-------------|-----------------------------------|---------------|
| PPLT00567 | Non-Dim | 120-277VAC to 24VDC, 36W, Class 2 | 1-3 |
| PPLT00586 | Non-Dim | 120-277VAC to 24VDC, 40W, Class 2 | 1-4 |
| PPLT00158 | Non-Dim | 120VAC to 24VDC, 100W, Class 2 | 1-10 |

For other power supply options consult factory.

ACCESSORIES

Installation



WCA22

Outer Casing
For solid ceilings (concrete)
Consult factory for regular ceilings




WGA02

Retaining Spring Clip
Use for ceilings 1/8"
min. to 3/8" max. thick

ACCESSORIES

Anti-Glare



Honeycomb Louvre

Built into the fixture
The honeycomb louvre can
be provided on all fixed optics
except for diffuse and elliptical
optics

Various



WNAP10A0

Anti-Fall Kit

PHOTOMETRIC DATA

See IES Files

Job Name/Date:

Fixture Type Designation: