

ALTOPIANO 1.6


Altopiano is a family of compact, recessed outdoor downlights available in 3 sizes, round or square, perfectly suitable for hospitality and residential sectors, as well as steam rooms, NOT saunas. Available in static white, as well as RGBW mixing and Dim to Warm. Altopiano 1.6 is the 3.9" round, Dim to Warm version.



TECHNICAL DATA

| | |
|---------------------------|---|
| Wattage / Input | 9W (350mA) |
| Power Supply | Remote, not included. See page 2. |
| Construction | Body: Thermally Conductive Technopolymer Trim: Stainless Steel Lens: Diffuse or Extra-clear Glass Cable Length: 1.64' standard |
| Ceiling Thickness | Works with ceilings 1/8" to 1" thick. For ceilings 3/64" to 5/64" thick, use spring clips. |
| CCT | Dim to Warm (1800-3000K) |
| CRI | >90 |
| Delivered Lumens | 372 lm (3000K, 27°) |
| Efficacy | 41.3 lm/W (3000K, 27°) |
| Optics | 6 Standard (see below) |
| Finishes | 5 Standard, Custom RAL on request |
| Fixture Dimensions | Ø3.86" x 3.54" h |
| Cut-out Size | Ø3.54" |
| Fixture Weight | 1.32 lbs |
| LED Source | 1 COB LED |
| Lumen Maintenance | 55,000 hrs L90, B10 (Ta 25°C) |
| Color Consistency | 3-Step MacAdam |
| Operating Temp. | -4°F to +113°F |
| IP Rating | IP66 |
| IK Rating | IK08 |

Fixture Dimensions



ORDERING INFORMATION

Example: AP16101001WOLF or AP16101001WOLF-ST. Accessories / Power Supplies ordered separately.

| AP1610 | 10 | | W | | | - | |
|---------|-------------|---|---|--|--|---|---|
| Model # | Power | Accessories | CCT | Optics | Finish | | |
| AP1610 | 10 - Remote | 00 - None 01 - Honeycomb 02 - Anti-Glare Shield <i>NOTE: Honeycomb Louvre and Anti-Glare Shield not available on 0D (Diffuse) or 0W (23°x64°)</i> | W - Dim to Warm <i>(1800-3000K)</i> | 0S - 22° 0M - 26° 0L - 37° 0K - 51° 0W - 22° x 65° 0D - Diffuse | H - Anthracite T - Cor-ten F - Gray E - White 7 - Primer C - Custom RAL <i>(consult factory for "C")</i> | | ST <i>NOTE: Add suffix if fixture is going to used in a steam room or sauna</i> |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES


350mA

| Part Number | Description | Input/Output | # of Fixtures |
|-----------------------------|---|---|---------------|
| PPLT00211 | Non-Dim | 120VAC to 350mA, 10W, Class 2 | 1-1 |
| PPLT00496 | Phase Dim (120V only) | 120VAC to 350mA, 12W, Class 2, DAMP | 1-1 |
| PPLT00465-P | 0-10V Dimming to 1.0% | 120-277VAC to 350mA, 20W, Class 2, DAMP | 1-2 |
| PPLT00263 | Leading / Trailing Edge Dimmable to 10% (120V only) | 120-277VAC to 350mA, 32W, Class 2 | 2-2 |
| PPLT00467-P | 0-10V Dimming to 1.0% | 120-277VAC to 350mA, 50W, Class 2, DAMP | 1-3 |
| PPLT00538-P | 0-10V Dimming to 0.1% | 120-277VAC to 350mA, 100W, Class 2 | 1-8 |

For other power supply options consult factory.

ACCESSORIES

Installation



WCA19-DP

IC / JA8 Housing




WGA02

Retaining Spring Clip
Use for ceilings 1/8"
min. to 3/8" max. thick

ACCESSORIES

Anti-Glare



Honeycomb Louvre

Built into the fixture
The honeycomb louvre can be provided on all fixed optics except for diffuse and elliptical optics



Anti-glare Shield

Built into the fixture
The anti-glare shield can be provided on all fixed optics except for diffuse and elliptical optics

Various



WNAP10A0
Anti-Fall Kit

PHOTOMETRIC DATA

See IES Files

Job Name/Date:

Fixture Type Designation: