

The invisible
recessed
projector.

mira 45 LT

design by Landa R&D

designplan® 

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042



mira 45 LT

Myra 45 LT is a recessed wall luminaire in extruded aluminum with anodized finish and additional construction quality that ensures extreme resistance to chemical and atmospheric agents, thus increasing the product lifetime.

This invisible recessed projector has a symmetrical 2W light beam with spot and flood optics, for maximum and complete versatility of application. Mira 45 LT is also ideal for in-ground installations.

MIRA 45 LT | FLOOR RECESSED Also Available





mira 45 LT


SPOT • FLOOD

| 2W




TECHNICAL SPECIFICATIONS

| | SPOT | FLOOD |
|---------------------------------------|--|--|
| Source lamp | LED 2W | LED 2W |
| Total wattage | 2W | 2W |
| Voltage | 24VDC | 24VDC |
| Control | Power supply not included • dimmable on request | Power supply not included • dimmable on request |
| Light color | 3000K • 4000K • other colors on request | 3000K • 4000K • other colors on request |
| Delivered lumens *Lumens at source | 118 lm (160 lm*) @ 3000K 118 lm (160 lm*) @ 4000K | 102 lm (160 lm*) @ 3000K 102 lm (160 lm*) @ 4000K |
| Luminous efficacy | 59 lm/W @ 3000K 59 lm/W @ 4000K | 51 lm/W @ 3000K 51 lm/W @ 4000K |
| McADAM steps | 3 | 3 |
| Beam | 12° | 35° |
| CRI | > 90 | > 90 |
| Life time | L70 > 50.000 h Ta 40°C | L70 > 50.000 h Ta 40°C |
| IP rating | IP66 | IP66 |
| IK rating | IK06 | IK06 |




| E (FC) | | | |
|--------|-------------|-------------|--------|
| H (ft) | fc (3000 K) | fc (4000 K) | ∅ (ft) |
| 3.28' | 105.5 | 105.5 | 0.66' |
| 6.56' | 26.4 | 26.4 | 1.31' |
| 9.84' | 11.7 | 11.7 | 1.97' |
| 13.12' | 6.6 | 6.6 | 2.95' |
| 16.40' | 4.2 | 4.2 | 3.61' |



| E (FC) | | | |
|--------|-------------|-------------|--------|
| H (ft) | fc (3000 K) | fc (4000 K) | ∅ (ft) |
| 3.28' | 21.6 | 21.6 | 0.02' |
| 6.56' | 5.4 | 5.4 | 0.05' |
| 9.84' | 2.4 | 2.4 | 0.07' |
| 13.12' | 1.4 | 1.4 | 0.10' |
| 16.40' | 0.8 | 0.8 | 0.12' |

MATERIALS

| | |
|-----------|-----------------------------|
| Body | Extruded aluminum EN AW6060 |
| Diffuser | Extra clear polycarbonate |
| Finishing | Anodized |



ORDER CODE

| | | | |
|------------|---------|-------------|------------------------|
| MI 2 0 000 | - | B 7 Z | - |
| | | Finishing | H Gray |
| | | | L Graphite |
| | | Light color | N 4000 K |
| | | | H 3000 K |
| | | Beam | S Spot |
| | | | F Flood |
| | Example | | MI 2 0 000 S N B 7 Z 1 |

INCLUDED ACCESSORIES

| Code | Description |
|------|----------------------------------|
| - | 3.28' (1 m) length cable -05RN-F |
| - | Housing box |

AVAILABLE ACCESSORIES

| Code | Description |
|----------|------------------------|
| 0409M009 | Single connection IP68 |





1534

