

The invisible
recessed
projector.

mira 45 LT

design by Landa R&D

designplan[®] 

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042



mira 45 LT

Myra 45 LT is a recessed wall luminaire in extruded aluminum with anodized finish and additional construction quality that ensures extreme resistance to chemical and atmospheric agents, thus increasing the product lifetime.

This invisible recessed projector has a symmetrical 2W light beam with spot and flood optics, for maximum and complete versatility of application. Mira 45 LT is also ideal for in-ground installations.

MIRA 45 LT | FLOOR RECESSED Also Available






mira 45 LT | 2W

SPOT • FLOOD




TECHNICAL SPECIFICATIONS

	SPOT	FLOOD
Source lamp	LED 2W	LED 2W
Total wattage	2W	2W
Voltage	24VDC	24VDC
Control	Power supply not included • dimmable on request	Power supply not included • dimmable on request
Light color	3000K • 4000K • other colors on request	3000K • 4000K • other colors on request
Delivered lumens *Lumens at source	118 lm (160 lm*) @ 3000K 118 lm (160 lm*) @ 4000K	102 lm (160 lm*) @ 3000K 102 lm (160 lm*) @ 4000K
Luminous efficacy	59 lm/W @ 3000K 59 lm/W @ 4000K	51 lm/W @ 3000K 51 lm/W @ 4000K
McADAM steps	3	3
Beam	12°	35°
CRI	> 90	> 90
Life time	L70 > 50.000 h Ta 40°C	L70 > 50.000 h Ta 40°C
IP rating	IP66	IP66
IK rating	IK06	IK06




E (FC)			
H (ft)	fc (3000 K)	fc (4000 K)	∅ (ft)
3.28'	105.5	105.5	0.66'
6.56'	26.4	26.4	1.31'
9.84'	11.7	11.7	1.97'
13.12'	6.6	6.6	2.95'
16.40'	4.2	4.2	3.61'



E (FC)			
H (ft)	fc (3000 K)	fc (4000 K)	∅ (ft)
3.28'	21.6	21.6	0.02'
6.56'	5.4	5.4	0.05'
9.84'	2.4	2.4	0.07'
13.12'	1.4	1.4	0.10'
16.40'	0.8	0.8	0.12'

MATERIALS

Body	Extruded aluminum EN AW6060
Diffuser	Extra clear polycarbonate
Finishing	Anodized



ORDER CODE

MI 2 0 000	-	B 7 Z	-
		Finishing	H Gray
			L Graphite
		Light color	N 4000 K
			H 3000 K
		Beam	S Spot
			F Flood
	Example		MI 2 0 000 S N B 7 Z 1

INCLUDED ACCESSORIES

Code	Description
-	3.28'(1 m) length cable -05RN-F
-	Housing box

AVAILABLE ACCESSORIES

Code	Description
0409M009	Single connection IP68





1534

