



SLOT

LAM32  
IDEASBECOMINGLIGHT

*Luminaire designed for floor installation, suitable for power LED sources. Its body is made of extruded aluminum welded to the base plate along all the circumference of the luminaire, polyester powder coated to ensure durability over time and maximum resistance against atmospheric agents. Internal LED housing is made of opal PMMA tubular and is completed by closing caps in anodized aluminum up to 18 microns and made tight by silicone gaskets and cable gland system. All the metal component of the luminaires of this series can be fully made of stainless steel AISI 316L, on request to ensuring full lasting stability even in presence of salt fog. The head signal light is optional and is composed of the capsule in opal PMMA. Power LED source is placed in a LED housing in turned aluminum anodized up to 18 microns. The installation is allowed thanks to not-included screws for the direct fixing to the floor, or through an anchor plate in stainless steel sheet with anchors bolts for the concrete. Integrated electronic power supply allows the connection of the luminaire to the power supply voltage. It is also equipped with a 19.7" neoprene cable for connection to the power supply line through appropriate connection systems to be ordered separately.*




designplan® 

79 Trenton Avenue  
Frenchtown, NJ 08825

[www.designplan.com](http://www.designplan.com)

Tel: (908) 996-7710  
Fax: (908) 996-7042

# SLOT




## TECHNICAL DRAWING

SLOT 1




Ø3.94" x H 13.78"

SLOT 2



Ø3.94" x H 37.40"

SLOT 3



Ø3.94" x H 61.02"

SLOT 1T



Ø3.94" x H 14.37"

SLOT 2T



Ø3.94" x H 37.99"

SLOT 3T




Ø3.94" x H 61.61"

## SLOT

model	code	lamp	lumens	
			3000K	4000K
SLOT 1	LM05.101221	LED 6W	930	975
SLOT 2	LM05.101222	LED 18W	2790	2925
SLOT 3	LM05.101223	LED 30W	4650	4830
SLOT 1T	LM05.101224	LED 8.2W	930+214	975+214
SLOT 2T	LM05.101225	LED 20.2W	2790+214	2925+214
SLOT 3T	LM05.101226	LED 32.2W	4650+214	4830+214

## EXAMPLE OF CODE COMPOSITION

05.101221.01.DI.BF.RE



Electronic driver 50-60Hz in-tegrated in the luminaire's body. Connec-tion systems to be ordered as accessories.

### Light beam

.DI	diffused
<b>Front LED color</b>	
.BP	3000K
.BF	4000K
<b>Top LED color</b>	
.RE	red
.GR	green
.BL	blue

## ACCESSORIES

### ANCHOR PLATE

	model	code	size
	SLOT 1-2 SLOT 1T-2T	LM20.100369	Ø5.91" H5.91"
	SLOT 3-3T	LM20.101235	Ø7.87" H11.81"

## FINISH

color	code	color	code	color	code
	.01 / painted white		.02 / painted black		.03 / painted gray
	.04 / painted cor-ten		.11 / painted anthracite		

