

FLAT EVO 3

LIGHT AT MOTION
LAMB32
IDEAS BECOMING LIGHT

MINIMUM MAXIMUM
LUMEN OUTPUT

designplan®

datasheet


Flat Evo is a surface-mounted, outdoor floodlight suitable for installation on walls, ceilings or floors. Flat Evo 3 has 8 LEDs and is available in 2 color temperatures and a variety of optics options including asymmetric.

TECHNICAL DATA

Wattage	17.6W (8 X 2.2W)
Power Supply	Remote 24VDC, not included. See page 2.
Construction	Body: Anticorodal Aluminum (Anodizing Treatment) Lens: Tempered, Extra Clear glass Cable Length: 1.64'
CCT	3000K, 4000K
BUG Rating	B2-U1-G0 (3000K, 25°)
Delivered Lumens	2040 lm (3000K) 2205 lm (4000K)
Efficacy	115.9 lm/W (3000K) 123.9 lm/W (4000K)
Optics	7 Available, See Below
Finishes	5 Standard, See Below
Fixture Dimensions	5.91" x 10.24" x 1.57" h
Color Consistency	<3-Step MacAdam
IP Rating	IP66
Impact Resistance	IK08



Fixture Dimensions



ORDERING INFORMATION

Example: LM07.104052.US.03.MD.BP. Accessories / Power Supplies ordered separately.

LM03.104052.US . . .

Model No.	Finish	Optic	CCT
LM03.104052.US (Flat Evo 3.0)	01 - White 02 - Black 03 - Aluminum 04 - Cor-ten 11 - Anthracite	SP - 10° MD - 25° FL - 40° RD - Road AS - Asym VE - Vert. Elliptical HE - Horiz. Elliptical	BP - 3000K BF - 4000K

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

Remote 24VDC Driver in NEMA Enclosure - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-4

For other power supply options consult factory.

ACCESSORIES



45° Screen
LM20.104188 - Flat Evo 3.0
5.9" x 8.7" x 6.7"



Protection Grid
LM20.104346 - Flat Evo 3.0
5.9" x 8.7"

Job Name/Date:

Fixture Type Designation:


PHOTOMETRIC DATA

Note: All photometric data is 3000K

Flat Evo 3

10°


Maximum Candela = 34659.6



PHOTOMETRIC FILENAME : FLAT EVO 3 LM03.104052.XX.SP.BP.IES

25°


Maximum Candela = 7770.1



PHOTOMETRIC FILENAME : FLAT EVO 3 LM03.104052.XX.MD.BP.IES

40°


Maximum Candela = 3757.6



PHOTOMETRIC FILENAME : FLAT EVO 3 LM03.104052.XX.FL.BP.IES

Asymmetric


Maximum Candela = 1440.4



PHOTOMETRIC FILENAME : FLAT EVO 3 LM03.104052.XX.AS.BP.IES

Road

Maximum Candela = 814.2



PHOTOMETRIC FILENAME : FLAT EVO 3 LM03.104052.XX.RD.BP.IES

Job Name/Date:

Fixture Type Designation: