

ROUND EVO 1


Round Evo is a round spotlight for outdoor installation on floors, walls or ceilings using adjustable stainless steel supports and accessories. Round Evo 1 has a diameter of 1.8", offered in 3 color temperature with 4 optics options, and 5 standard finishes.



TECHNICAL DATA

Wattage / Input	2.2W
Power Supply	Remote, not included. Consult Factory.
Construction	Body: Anticorodal Aluminum (<i>Anodizing Treatment</i>) Lens: Tempered, Extra Clear Glass Cable Length: 1.64'
CCT	2700K, 3000K, 4000K
BUG Rating	B0-U1-G0 (3000K)
Delivered Lumens	214 lm (3000K)
Efficacy	97.3 lm/W (3000K)
Optics	8°, 12°, 25°, 40°
Finishes	5 Standard, See Below
Fixture Dimensions	Ø1.77" x 2.95" h
Color Consistency	<3-Step MacAdam
IP Rating	IP66
Impact Resistance	IK08

Fixture Dimensions



ORDERING INFORMATION

Example: **LM03.103807.US.01.SP.BP**. Accessories / Power Supplies ordered separately.

LM03.103807.US			
Model No.	Finish	Optic	CCT
LM03.103807.US (Round Evo 1.0)	01 - White 02 - Black 03 - Aluminum 04 - Cor-ten 11 - Anthracite	SS - 8° SP - 12° MD - 25° FL - 40°	BC - 2700K BP - 3000K BF - 4000K

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

Consult Factory

ACCESSORIES



Spike for furniture or ground installation

LM20.104312
1.73" x 11.26" h



Clasp for furniture installation


LM20.104318
2.76" x 1.97"

PHOTOMETRIC DATA

Note: All photometric data is 3000K

12°


Maximum Candela = 3316.2



PHOTOMETRIC FILENAME : ROUND EVO 1 30K 12° - LM03.103807.XX.SP.BP.IES

25°


Maximum Candela = 724.5



PHOTOMETRIC FILENAME : ROUND EVO 1 30K 25° - LM03.103807.XX.MD.BP.IES

40°

Maximum Candela = 376.5



PHOTOMETRIC FILENAME : ROUND EVO 1 30K 40° - LM03.103807.XX.FL.BP.IES

Job Name/Date:

Fixture Type Designation: