




Technical features









701201P

# CYLINDER MICRO COB

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 1 COB CREE "CXB 1304" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
cob led	 18°	620	103.33
cob led	 36°	600	100.00
cob led	 60°	580	96.67
<b>4000°K neutral-white</b>			
cob led	 18°	640	106.67
cob led	 36°	620	103.33
cob led	 60°	600	100.00


Finish color options:



Technical data

Wattage	6 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x COB CREE "CXB 1304" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	2.20 lbs

AC090  
HONEYCOMB LOUVER






Technical features



701202P

# CYLINDER MINI COB

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 1 COB CREE "CXB 1310" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
cob led	14°	1,100	110
cob led	35°	1,060	106
cob led	55°	1,000	100
<b>4000°K neutral-white</b>			
cob led	14°	1,200	120
cob led	35°	1,140	114
cob led	55°	1,083	108


Finish color options:



Technical data

Wattage	10 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x COB CREE "CXB 1304" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	5.95 lbs

AC091  
HONEYCOMB LOUVER






701205P

# CYLINDER MINI HP

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 1 x CREE "XHP35" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	4°	690	86.25
high-power led	10°	662	82.75
high-power led	28°	642	80.25
<b>4000°K neutral-white</b>			
high-power led	4°	703	87.88
high-power led	10°	676	84.50
high-power led	28°	656	82.00

#### Finish color options:

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matt Black  
(on request)


#### Technical features



#### Technical data

Wattage	8 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x CREE "XHP35" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	5.95 lbs

AC091  
HONEYCOMB LOUVER











701203P

# CYLINDER MEDIUM COB

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 1 COB CREE "CXB 1512" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
cob led	14°	1,900	118.75
cob led	35°	1,813	113.31
cob led	55°	1,722	107.62
<b>4000°K neutral-white</b>			
cob led	14°	2,000	125.00
cob led	35°	1,900	118.75
cob led	55°	1,805	112.81

**Finish color options:**

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matt Black  
(on request)

**Technical features**

IP 66

IK 09

5 YEARS

0-10V


DALI


NEW

**Technical data**

Wattage	16 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x COB CREE "CXB 1512" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	8.82 lbs

AC092  
HONEYCOMB LOUVER






701206P

## CYLINDER MEDIUM HP

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 3 x CREE "XHP35" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	4°	2,050	102.50
high-power led	10°	2,000	100.00
high-power led	28°	1,950	97.50
<b>4000°K neutral-white</b>			
high-power led	4°	2,100	105.00
high-power led	10°	2,050	102.50
high-power led	28°	2,000	100.00

### Finish color options:

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matt Black  
(on request)


### Technical features



### Technical data

Wattage	20 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminium
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	3 x CREE "XHP35" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	8.82 lbs

AC092  
HONEYCOMB LOUVER













701204P

## CYLINDER MAXI COB

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 1 COB CREE "CXB 2540" LED. IP66 rating.




light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
cob led	14°	4,950	117.85
cob led	35°	4,752	113.14
cob led	55°	4,560	108.57
<b>4000°K neutral-white</b>			
cob led	14°	5,265	125.36
cob led	35°	5,000	119.05
cob led	55°	4,770	113.57

### Finish color options:

- Textured Grey  
RAL 9006
- Anthracite Grey  
RAL 7016
- Matt Black  
(on request)


### Technical features



### Technical data

Wattage	42 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	1 x COB CREE "CXB 2540" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	11.02 lbs

AC093  
HONEYCOMB LOUVER







701207P

# CYLINDER MAXI HP

Surface mounted luminaire for outdoor ceiling installation. Phospho-chromatized and polyester powder coated extruded copper-free aluminum body, tempered safety glass, molded silicone gaskets, with screws in stainless steel. Built-in LED driver, with 6 x CREE "XHP35" LED. IP66 rating.



light source	light beam options	lumen output (lm)	lumin. efficacy (lm/w)
<b>3000°K warm-white</b>			
high-power led	4°	4,300	113.15
high-power led	10°	4,260	112.10
high-power led	28°	4,210	110.79
<b>4000°K neutral-white</b>			
high-power led	4°	4,400	115.79
high-power led	10°	4,360	114.74
high-power led	28°	4,310	113.42

### Finish color options:

-  Textured Grey  
RAL 9006
-  Anthracite Grey  
RAL 7016
-  Matt Black  
(on request)

### Technical features



### Technical data

Wattage	38 WATT
IP Rating	IP66
IK Rating	IK09
Material	Phospho-chromatized and polyester powder coated extruded copper-free aluminum
Coating	Polyester powder coating with phosphochromating pre-finish
Light source	6 x CREE "XHP35" LED
Screws	Stainless steel
Transformer	Electrical power supply 120VAC 50/60Hz built-in
Gasket	Silicone rubber
Glass	Tempered
Power cable	3.28' power cable included
Gross weight	11.02 lbs

AC093  
HONEYCOMB LOUVER

