

L1 NANO 48V


L1 Nano 48V is a linear LED module for interiors, suitable to be installed on a 48V track. It is available in two lengths (26.5" and 46.2") with a black finish. L1 is composed of a high efficiency LED and an opal closure screen which diffuses an even light in the space where it is installed.



TECHNICAL DATA

| | |
|---------------------------|--|
| Wattage / Input | 6W (BUT048L00019) 12W (BUT048L00020) |
| Track Power Supply | Remote 48VDC power supply for track, not included. See 48V Track datasheet |
| Track Head | Integral 48V LED Converter in Track Adapter |
| Dimming Protocol | Non-Dim, Dali |
| Construction | Body: Aluminum Lens: Opal Diffused |
| CCT | 2700K, 3000K, 4000K |
| CRI | >90 |
| Delivered Lumens | 429 lm (BUT048L00019) 858 lm (BUT048L00020) |
| Efficacy | 71.5 lm/W (3000K) |
| Optics | Opal Diffuse |
| UGR Rating | <29 |
| Finishes | Black |
| Fixture Dimensions | 0.39" w x 26.5" or 46.2" l |
| Fixture Weight | 0.22 lbs (BUT048L00019) 0.33 lbs (BUT048L00020) |
| IP Rating | IP20 |

Fixture Dimensions



ORDERING INFORMATION

Example: **BUT048L00019W10030ND0.US**. Power Supplies ordered separately.

| | | | | | | |
|--|-------------------|--------------------------|---|--|----------|-----------|
| | B1 | 00 | | | 0 | US |
| Model No. | Finish | Optic | CCT | Dimmability | | |
| BUT048L00019 (26.5" l) BUT048L00020 (46.2" l) | B1 - Black | 00 - Opal Diffuse | 27 - 2700K 30 - 3000K 40 - 4000K | ND - Non Dimmable DA - DALI | 0 | US |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES


48VDC - See Track Datasheets

48V NANO TRACKS

N10




N-INSIDE



See N10 Track datasheet for ordering code and power supply



See N-Inside Track datasheet for ordering code and power supply



PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: