


MiniMag is a mini, recessed LED downlight with small proportions (Ø1.2"), great performance, and easy installation. It is available with mud in or fixing spring installation, 4 color temperatures, 4 optics options and 8 finishes.



TECHNICAL DATA

Wattage / Input	1.9W (700mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: Aluminum
CCT	2700K, 3000K, 3500K, 4000K
CRI	>80 (>97 on request)
Delivered Lumens	210 lm (3000K)
Efficacy	110.2 lm/W
Optics	16°, 35°, 35°x15°, 60°
Finishes	Black or White as standard 6 other finishes on request
Fixture Dimensions	Ø1.2" x 1.6" h (magnet 0.12" h)
Cutout Dimensions	Ø1.4" (with accessory B) Ø1.8" (with accessory R)
Lumen Maintenance	60,000 hrs L90, B10 (Ta 25°C) 100,000 hrs L70, B50 (Ta 25°C)
IP Rating	IP40
Impage Resistance	IK08

Fixture Dimensions:



ORDERING INFORMATION

Example: HRMM70XMDBLL.US. Accessories / Power Supplies ordered separately.

HRMM70				.US
Model No.	CCT	Optics	Finish	
HRMM70	WW - 2700K W - 3000K X - 3500K N - 4000K	ST - 16° MD - 35° EL - 35°x15° LA - 60°	WI - White Irazu BLL - Black Lava SB - Silver Bambalai (on request) BL - Bronze Lario (on request) RR - Rust Rame (on request) BF - Beige Futura (on request) GK - Gold Karkar (on request) BT - Blue Telica (on request)	.US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

700mA


Part Number	Description	Input/Output	Fixtures
PPLT00199	0-10V Dimming to 10%	120-277VAC to 700mA, 6W, Class 2, IP67	2-2
PPLT00470	Phase Dim (120V only)	120VAC to 700mA, 14W, Class 2	4-5
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 20W, Class 2	2-10
PPLT00261	Leading / Trailing-Edge Dimming to 10% (120V only)	120-277VAC to 700mA, 32W, Class 2	11-12
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 50W, Class 2, DAMP	2-15
PPLT00538-P	0-10V Dimming to 0.1% (4 channels)	120-277VAC to 700mA, 100W, Class 2	2-13 (2-52)

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00512	LTEA2W	LTEA	100%-1%	Hi-Lume™ 1% 2-Wire LED Driver (120V forward phase only)	120VAC to 700mA, 14W, Class 2	5-5
PPLT00515	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 14W, Class 2	5-5
PPLT00635	PEQ0E	PEQ0	100%-1%	Hi-Lume™ Premier 0.1% EcoSystem LED Driver	120/277VAC to 700mA, 20W, Class 2	6-7
PPLT00278	LTEA2W	LTEA	100%-1%	Hi-Lume™ 1% 2-Wire LED Driver (120V forward phase only)	120VAC to 700mA, 27W, Class 2	8-10
PPLT00517	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 27W, Class 2	8-10

For other power supply options consult factory.

ACCESSORIES - Installation



HRMTB1

Accessory B - with Fixing Spring

Standard:

- **WI:** White Irazu
- **BLL:** Black Lava



On request:

- **SB:** Silver Bombalai
- **BL:** Bronze Lario
- **RR:** Rust Rame
- **BF:** Beige Futura
- **GK:** Gold Karkar
- **BT:** Blue Telica










Extraction Tool

Included with fixture



PHOTOMETRIC DATA

Coming Soon



HRMTR1

Accessory R
Mud In (White)

HRMTR2

Accessory R
Mud In (White)

HRMTR3

Accessory R
Mud In (White)

HRMTR4

Accessory R
Mud In (White)

Job Name/Date:

Fixture Type Designation: