

TECHNICAL CATALOG 2024

designplan[®] 

STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042



Inox Natural



Inox Graphite



Inox Bronze

CRI>80

IP66

IK08




Bollard available in two heights, 1.97 feet and 2.95 feet, in stainless steel AISI 316L. The bollard head is available in versions with diameters of 3.54 inches or 4.72 inches to meet different design requirements. Optics include 21°, 45°, and 65° with color temperatures of 2700K, 3000K, and 4000K. Extra-clear black silk-screened tempered glass, 0.16 inches thick. Installation on a flange with anchor bolts for concrete application, or alternatively, with a plate for fixing with anchors. Integrated power supply. Surface finish HCT available in three variants.



23.62"

5.71"



3.54"

5.71"


Emission



21°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power
5W



45°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power
5W



65°


Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm

Power
5W




Accessories



IP66 IK08 lm



ANCHOR FLANGE
PT64010




ANCHOR BOLTS
KIT
PT64000



35.43"

5.71"



3.54"

5.71"


Emission



21°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power
5W



45°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power
5W



65°


Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm

Power
5W




Accessories

IP66 IK08 lm



ANCHOR FLANGE

PT64010




ANCHOR BOLTS
KIT

PT64000



7.01"

23.62"



7.01"

4.72"


Emission



21°

Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm



Power
7W



45°

Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm


Power
7W



65°


Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm

Power
7W




Accessories


IP66 IK08 lm



ANCHOR FLANGE
PT64010




ANCHOR BOLTS
KIT
PT64000



35.43"

7.01"



7.01"

4.72"


Emission



21°

Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm


Power
7W



45°

Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm


Power
7W



65°


Color	2700K	3000K	4000K
	741 lm	750 lm	836 lm

Power
7W




Accessories

IP66 IK08 lm



ANCHOR FLANGE

PT64010



ANCHOR BOLTS
KIT

PT64000