

datasheet







Fixture Dimensions - See page 2

TECHNICAL DATA

Treatment finishes. Lamp by others.

Wattage / Input	5W LED (Lamp by others)		
Power Supply	Remote 12VDC Constant Voltage		
Dimming	See Power Supplies on Page 2		
Construction	Body: AISI 316L Stainless Steel Lens: Extra-clear Tempered Glass 0.16" Thick		
ССТ	MR11 (D-50) Lamp by others MR16 (D-70) Lamp by others		
Delivered Lumens	Determined by Lamp		
Efficacy	Determined by Lamp		
Optics	Determined by Lamp		
Hard Coat Finishes	Inox Natural, Inox Graphite, Inox Bronze		
Fixture Dimensions	Ø2.2" x 7.9", 15.8", 31.5" h (Focal D-50) Ø2.8" x 7.9", 15.8", 31.5" h (Focal D-70)		
IP Rating	IP66		
Impact Resistance	IK08		

Focal is a IP66-rated LED floodlight with locking ring, parallel lines, and a

architectural details and natural elements such as shrubs and planted areas. It is available in 2 head sizes, 3 heights, and in 3 standard Hard Coat

head axial rotation of 180°, that is perfectly suited for illuminating

Hard Coating Treatment is the surface treatment of all the products by Stral Lighting. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain.

ORDERING INFORMATION

Example: SPT5041034B.US. Power Supplies / Accessories sold separately.


				.US
Model No.	Height	Finishes	Fixing	
SPT501504 (D-50 - 5W LED Bulb)	2 - 7.87"	N - Inox Natural	F - On Mounting Plate	.US
SPT501701 (D-70 - 5W LED Bulb)	4 - 15.75"	G - Inox Graphite	S - On Spike (included)	
Bulb Sold Separately	8 - 31.50"	B - Inox Bronze		

Job Name/Date: Fixture Type Designation:



datasheet

FIXTURE DIMENSIONS







H1




H2


2.8"





FOCAL D-70





SUGGESTED POWER SUPPLIES

12VDC

Part Number	Description	Input/Output	# of Fi D-50	# of Fixtures 60 D-70	
PPLT00162	Non-Dim	120VAC to 12VDC, 20W, Class 2, IP64	1-5	1-3	
PPLT00654	0-10V Dimming	120-277VAC to 12VDC, 50W, Class 2	1-13	1-8	

For other power supply options consult factory.

FINISHES



Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042