


IDRIA WALL is a wall mounted LED luminaire made of Accoya®, a sustainable, highly durable wood treated with Acetylation treatment. It is available with 8W total power and diffuse optics, and can be used as an uplight or downlight. 25 year warranty on Accoya® Wood - 5 year warranty on lighting element.



TECHNICAL DATA

Wattage	5.5W LED, 8W Total
Power Supply	Remote 700mA, not included. See page 2
Construction	Body: Accoya® Wood and Inox AISI 316L Lens: Opal Polycarbonate
CCT	3000K
BUG Rating	Coming Soon
CRI	>90
Delivered Lumens	542 lm
Efficacy	68 lm/W
Optics	Diffuse
Finishes	Accoya® - Acetylation treatment
Fixture Dimensions	6.5" x 6.5" x 2.4" h
Lumen Maintenance	L70 >50,000hrs (Ta 40°C)
Color Consistency	3-Step MacAdam
IP Rating	IP65
Impact Resistance	IK08

Fixture Dimensions



ORDERING INFORMATION

Example: **LNID80PARDHB103.US**. Power Supply sold separately.

LNID	80PAR	D	HB103	US
Model No.	Size	Optics	Power	
LNID	80PAR	D - Diffuse	HB103	US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

700mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00470	Phase Dim (120V only)	120VAC to 700mA, 14W, Class 2, IP66	1-1
PPLT00656-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 20W, Class 2, IP20	1-2
PPLT00261	Leading / Trailing Edge Dimming to 10% (120V only)	120-277VAC to 700mA, 32W, Class 2	2-3
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 700mA, 50W, Class 2, DAMP	1-4
PPLT00538-P	0-10V Dimming to 0.1% (4 channels)	120-277VAC to 700mA, 100W, Class 2	1-3 (1-12)

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00515	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 14W, Class 2	1-1
PPLT00517	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 27W, Class 2	2-3
PPLT00181	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 700mA, 38W, Class 2	3-4

*For other power supply options consult factory.***ACCESSORIES - Installation***(included)***Single Connection IP68****PHOTOMETRIC DATA - Coming Soon***Note: All photometric data is 3000K**Job Name/Date:**Fixture Type Designation:*