


IDRIA WALL is a wall mounted LED luminaire made of Accoya®, a sustainable, highly durable wood treated with Acetylation treatment. It is available with 8W total power and diffuse optics, and can be used as an uplight or downlight. 25 year warranty on Accoya® Wood - 5 year warranty on lighting element.



TECHNICAL DATA

| | |
|---------------------------|---|
| Wattage | 8W |
| Power Supply | Remote 500mA, not included. See page 2 |
| Construction | Body: Accoya® Wood and Inox AISI 316L Lens: Opal Polycarbonate |
| CCT | 2700K, 3000K |
| BUG Rating | Coming Soon |
| CRI | >90 |
| Delivered Lumens | 542 lm (3000K) |
| Efficacy | 68 lm/W |
| Optics | Diffuse |
| Finishes | Accoya® - Acetylation treatment, Clear or Gray |
| Fixture Dimensions | 6.5" x 6.5" x 2.4" h |
| Lumen Maintenance | L70 >50,000hrs (Ta 40°C) |
| Color Consistency | 3-Step MacAdam |
| IP Rating | IP65 |
| Impact Resistance | IK08 |

Fixture Dimensions



ORDERING INFORMATION

Example: **LNID80PARDHBBZ3.US**. Power Supply sold separately.

| | | | | | | |
|------------------|--------------|---------------|------------------------|--------------|---------------------------------------|-----------|
| LNID | 80PAR | D | | BBZ | | US |
| Model No. | Size | Optics | CCT | Power | Finish | |
| LNID | 80PAR | D - Diffuse | Y - 2700K H - 3000K | BBZ - Remote | 3 - Accoya® Clear 4 - Accoya® Gray | US |

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

| Part Number | Description | Input/Output | # of Fixtures |
|-----------------------------|--|---|---------------|
| PPLT00466-P | | 120-277VAC to 500mA, 10W, Class 2, DAMP | 1-1 |
| PPLT00469 | Phase Dim (120V only) | 120VAC to 500mA, 14W, Class 2, IP66 | 1-2 |
| PPLT00656-P | 0-10V Dimming to 1.0% | 120-277VAC to 500mA, 20W, Class 2, IP20 | 1-3 |
| PPLT00262 | Leading / Trailing Edge Dimming to 10% (120V only) | 120-277VAC to 500mA, 32W, Class 2 | 2-3 |
| PPLT00467-P | 0-10V Dimming to 1.0% | 120-277VAC to 500mA, 50W, Class 2, DAMP | 1-4 |
| PPLT00538-P | 0-10V Dimming to 0.1% (4 channels) | 120-277VAC to 500mA, 100W, Class 2 | 1-4 (1-16) |

Suggested Lutron Compatible

| Part Number | Option | Lutron SKU | Dim Range | Description | Input/Output | # of Fixtures |
|---------------------------|----------------|------------|-----------|--|-----------------------------------|---------------|
| PPLT00259 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 14W, Class 2 | 1-1 |
| PPLT00195 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 19W, Class 2 | 2-3 |
| PPLT00676 | PEQ0E | PEQ0 | 100%-0.1% | Hi-Lume™ Premier 0.1% EcoSystem™ LED Driver | 120-277VAC to 500mA, 20W, Class 2 | 1-3 |
| PPLT00180 | L3DAE / L3DA3W | L3DA | 100%-1% | Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver | 120-277VAC to 500mA, 27W, Class 2 | 3-4 |

For other power supply options consult factory.

ACCESSORIES - Installation

(included)

Single Connection IP68

PHOTOMETRIC DATA - Coming Soon

Note: All photometric data is 3000K

Job Name/Date:

Fixture Type Designation: