

A HABITAT OF LIGHT.



# designplan®





## idria

Idria is a range which can be integrated into any outdoor space. Both the bollard and the wall version have a power of 8W, ideal for lighting paths and entrances in a decisive, scenic and evocative way. The products are made in Accoya<sup>®</sup> together with AISI 316L stainless steel and are characterized in both versions by a diffused light emission.



### designplan®

 $L \land N \supset \land$ 

### idria

#### WALL LAMP



Wattage 8W Voltage 500mA Beam

#### TECHNICAL SPECIFICATIONS

Source lamp	
Total wattage	
Voltage	
Control	
Light color	

Luminous flux (\*Source fl

Luminous efficacy McADAM steps

Beam

CRI


Life time IP rating IK rating


500mA, 50-60 Hz	
On/Off	
3000K • other colors on request	
542 lm (759 lm*)	
68 lm/W	
3	
Diffuse	
> 90	
L70 > 50.000 h Ta 40°C	
IP65	
IK08	

DIFFUSE

LED 5.5W

8W









# designplan

#### MATERIALS

Body Diffuser Finishing Accoya® wood and inox AISI 316L Opal polycarbonate Acetylation treatment

#### ORDER CODE

ID 8 0 PAR D H B B Z 3

#### INCLUDED ACCESSORIES

Code	Description
	Single connection IP68

 $L \land N \supset \land$ 

## idria

BOLLARD



Wattage 8W 500mA Voltage Beam

#### TECHNICAL SPECIFICATIONS

Source lamp Total wattage

Voltage Control

Light color

Luminous efficacy McADAM steps


Beam


CRI

Life time IP rating

IK rating

LED 5	5W
8W	
500m/	A, 50-60 Hz
On/Of	F
3000k	• other colors on request
542 Im	(759 lm*)
68 lm/	W
3	
Diffus	e
> 90	
L70 > !	50.000 h Ta 40°C
IP65	
IK08	









# designplan®

#### MATERIALS

Body	Accoya® wood and inox AISI 316L
Diffuser	Opal polycarbonate
Finishing	Acetylation treatment

#### ORDER CODE



060	23.62 in	
090	35.43 in	
120	47.24 in	

Example ID 8 0 060 D H B B Z 3

#### INCLUDED ACCESSORIES

Code	Description
	Single connection IP68
	Root mounting kit

