

idria

design by Landa R&D



A HABITAT OF LIGHT.



# idria

Idria is a range which can be integrated into any outdoor space. Both the bollard and the wall version have a power of 8W, ideal for lighting paths and entrances in a decisive, scenic and evocative way. The products are made in Accoya® together with AISI 316L stainless steel and are characterized in both versions by a diffused light emission.



**WALL LAMP**



Wattage 8W

Voltage 500mA

Beam 

**TECHNICAL SPECIFICATIONS**

Source lamp	<u>LED 5.5W</u>
Total wattage	<u>8W</u>
Voltage	<u>500mA, 50-60 Hz</u>
Control	<u>On/Off</u>
Light color	<u>3000K • other colors on request</u>
Luminous flux (*Source flux)	<u>542 lm (759 lm*)</u>
Luminous efficacy	<u>68 lm/W</u>
McADAM steps	<u>3</u>
Beam	<u>Diffuse</u>
CRI	<u>&gt; 90</u>
Life time	<u>L70 &gt; 50.000 h Ta 40°C</u>
IP rating	<u>IP65</u>
IK rating	<u>IK08</u>

**DIFFUSE**

<u>LED 5.5W</u>
<u>8W</u>
<u>500mA, 50-60 Hz</u>
<u>On/Off</u>
<u>3000K • other colors on request</u>
<u>542 lm (759 lm*)</u>
<u>68 lm/W</u>
<u>3</u>
<u>Diffuse</u>
<u>&gt; 90</u>
<u>L70 &gt; 50.000 h Ta 40°C</u>
<u>IP65</u>
<u>IK08</u>

**MATERIALS**




Body	<u>Accoya® wood and inox AISI 316L</u>
Diffuser	<u>Opal polycarbonate</u>
Finishing	<u>Acetylation treatment</u>

**ORDER CODE**

**ID 8 0 PAR D H B B Z 3**

**INCLUDED ACCESSORIES**

Code	Description
-	<u>Single connection IP68</u>



# idria

## BOLLARD



Wattage 8W

Voltage 500mA

Beam 

### TECHNICAL SPECIFICATIONS

Source lamp	<u>LED 5.5W</u>
Total wattage	<u>8W</u>
Voltage	<u>500mA, 50-60 Hz</u>
Control	<u>On/Off</u>
Light color	<u>3000K • other colors on request</u>
Luminous flux (*Source flux)	<u>542 lm (759 lm*)</u>
Luminous efficacy	<u>68 lm/W</u>
McADAM steps	<u>3</u>
Beam	<u>Diffuse</u>
CRI	<u>&gt; 90</u>
Life time	<u>L70 &gt; 50.000 h Ta 40°C</u>
IP rating	<u>IP65</u>
IK rating	<u>IK08</u>

### DIFFUSE

LED 5.5W
8W
500mA, 50-60 Hz
On/Off
3000K • other colors on request
542 lm (759 lm*)
68 lm/W
3
Diffuse
> 90
L70 > 50.000 h Ta 40°C
IP65
IK08

### MATERIALS

Body	<u>Accoya® wood and inox AISI 316L</u>
Diffuser	<u>Opal polycarbonate</u>
Finishing	<u>Acetylation treatment</u>

### ORDER CODE

**ID 8 0**     **DHBBZ 3**

Height	<u>060</u>	<u>23.62 in</u>
	<u>090</u>	<u>35.43 in</u>
	<u>120</u>	<u>47.24 in</u>

Example ID 8 0 060 DHBBZ 3

### INCLUDED ACCESSORIES

Code	Description
-	<u>Single connection IP68</u>
-	<u>Root mounting kit</u>

