SOLISIA WALL 200



datasheet


SOLISIA WALL 200 is a round, wall mounted LED luminaire made of Accoya®, a sustainable, highly durable wood treated with Acetylation treatment. It is available with 12W, 3000K and diffuse optics. 25 year warranty on Accoya® Wood - 5 year warranty on lighting element.

TECHNICAL DATA

TEOTIMORE DATA			
Wattage	12W		
Power Supply	Remote 24VDC, not included. See page 2.		
Construction	Body: Accoya® Wood and Inox AISI 316L Lens: Opal Polycarbonate		
ССТ	3000K		
CRI	>90		
Delivered Lumens	1098 lm		
Efficacy	91.5 lm/W		
Optics	Diffuse		
Finishes	Accoya® - Acetylation treatment		
Fixture Dimensions	Ø7.87" x 1.18" h		
Lumen Maintenance	L70 >50,000hrs (Ta 40°C)		
Color Consistency	3-Step MacAdam		
IP Rating	IP65		
Impact Resistance	IK08		



Fixture Dimensions



ORDERING INFORMATION

Example: LNSO80055DHB7Z3.US. Accessories / Power Supplies ordered separately.

80PAR	D	HB7Z3	US
Size	Optics	Power	
80PAR	D - Diffuse	HB7Z3	US
	Size	Size Optics	Size Optics Power

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042



datasheet

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00680	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 20W, Class 2, IP66	1-1
PPLT00155	Non-Dim	120VAC to 24VDC, 30W, Class 2	1-2
PPLT00157	Non-Dim	120VAC to 24VDC, 60W, Class 2	1-4
PPLT00627	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 96W, Class 2, IP67	1-6
PPLT00158	Non-Dim	120VAC to 24VDC, 100W, Class 2	1-6
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-6

For other power supply options consult factory.

ACCESSORIES - Installation


(included)

Single Connection IP68

PHOTOMETRIC DATA

Note: All photometric data is 3000K

Maximum Candela = 352.2



PHOTOMETRIC FILENAME: SOLISIA_SO80XXXDHB7Z3.IES

Job Name/Date:

Fixture Type Designation: