

TECHNICAL CATALOG 2024

designplan[®] 

STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

FIXED



Inox Natural



Inox Graphite



Inox Bronze



CRI>80

IP66

IK08



The spacer integrated with the lamp body makes the product compact. Made of stainless steel AISI 316L. Extra-clear black silk-screened tempered glass, 0.16 inches thick. Available in single and dual emission versions with one, two, or three LEDs to meet different design requirements. Optics include 21°, 45°, 65°, asymmetric, and street optics with color temperatures of 2700K, 3000K, and 4000K; the latter two optics are available only for single emission versions. Integrated power supply. Surface finish HCT available in three variants.




Emission



21°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |


Power
5W



45°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |


Power
5W





65°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |

Power
5W



IP66 IK08 lm




Emission



21°

| Color | | |
|---------|---------|---------|
| 2700K | 3000K | 4000K |
| 1086 lm | 1100 lm | 1226 lm |


Power
10W



45°

| Color | | |
|---------|---------|---------|
| 2700K | 3000K | 4000K |
| 1086 lm | 1100 lm | 1226 lm |


Power
10W





65°

| Color | | |
|---------|---------|---------|
| 2700K | 3000K | 4000K |
| 1086 lm | 1100 lm | 1226 lm |

Power
10W



IP66 IK08 lm




Emission



21°

| Color | 2700K | 3000K | 4000K |
|-------|---------|---------|---------|
| | 1629 lm | 1650 lm | 1839 lm |


Power
15W



45°

| Color | 2700K | 3000K | 4000K |
|-------|---------|---------|---------|
| | 1629 lm | 1650 lm | 1839 lm |


Power
15W





65°

| Color | 2700K | 3000K | 4000K |
|-------|---------|---------|---------|
| | 1629 lm | 1650 lm | 1839 lm |

Power
15W



IP66 IK08 lm




Emission



Street

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |


Power
5W





Asym.

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |

Power
5W



IP66 IK08 lm




Emission



Street

| Color | 2700K | 3000K | 4000K |
|-------|---------|---------|---------|
| | 1087 lm | 1100 lm | 1227 lm |


Power
10W





Asym.

| Color | 2700K | 3000K | 4000K |
|-------|---------|---------|---------|
| | 1087 lm | 1100 lm | 1227 lm |

Power
10W



IP66 IK08 lm




Emission



Street

| Color | | |
|---------|---------|---------|
| 2700K | 3000K | 4000K |
| 1087 lm | 1100 lm | 1227 lm |


Power
10W




Asym.

| Color | | |
|---------|---------|---------|
| 2700K | 3000K | 4000K |
| 1087 lm | 1100 lm | 1227 lm |

Power
10W




IP66 IK08 lm



4.72"

4.72"



4.72"

2.36"


Emission



21° + 21°

| Color | | |
|----------|----------|----------|
| 2700K | 3000K | 4000K |
| 2x543 lm | 2x550 lm | 2x613 lm |


Power
2x5W



45° + 45°

| Color | | |
|----------|----------|----------|
| 2700K | 3000K | 4000K |
| 2x543 lm | 2x550 lm | 2x613 lm |


Power
2x5W




65° + 65°

| Color | | |
|----------|----------|----------|
| 2700K | 3000K | 4000K |
| 2x543 lm | 2x550 lm | 2x613 lm |

Power
2x5W




IP66 IK08 lm



6.30"

4.72"



6.30"

2.36"


Emission



21° + 21°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1086 lm | 2x1100 lm | 2x1226 lm |


Power
2x10W



45° + 45°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1086 lm | 2x1100 lm | 2x1226 lm |


Power
2x10W





65° + 65°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1086 lm | 2x1100 lm | 2x1236 lm |

Power
2x10W



IP66 IK08 lm




Emission



21° + 21°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1629 lm | 2x1650 lm | 2x1839 lm |


Power
2x15W



45° + 45°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1629 lm | 2x1650 lm | 2x1839 lm |


Power
2x15W



65° + 65°

| Color | | |
|-----------|-----------|-----------|
| 2700K | 3000K | 4000K |
| 2x1629 lm | 2x1650 lm | 2x1839 lm |

Power
2x15W



IP66 IK08 lm