

TECHNICAL CATALOG 2024

designplan[®] 

STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

FLEX



Inox Natural



Inox Graphite



Inox Bronze



CRI>80

IP66

IK08



The spacer integrated with the lamp body makes the product compact. Adjustable bracket to allow movements in all directions. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 0.16 inches thick. Single-emission versions with one, two or three LEDs for different design needs. 21°, 45° and 65° optics at 2700K, 3000K and 4000K. Integrated power supply. HCT surface finish available in three variants.




Emission



21°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |


Power
5W



45°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |


Power
5W





65°

| Color | 2700K | 3000K | 4000K |
|-------|--------|--------|--------|
| | 543 lm | 550 lm | 613 lm |

Power
5W



IP66 IK08 Im Orientable




Emission



21°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1086 lm | 1100 lm | 1226 lm | |


Power
10W



45°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1086 lm | 1100 lm | 1226 lm | |


Power
10W





65°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1086 lm | 1100 lm | 1226 lm | |

Power
10W



- IP66
- IK08
- lm
- Orientable




Emission



21°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1629 lm | 1650 lm | 1839 lm | |


Power
15W



45°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1629 lm | 1650 lm | 1839 lm | |


Power
15W



65°

| Color | 2700K | 3000K | 4000K |
|---------|---------|---------|-------|
| 1629 lm | 1650 lm | 1839 lm | |

Power
15W



IP66 IK08 lm Orientable