

# TECHNICAL CATALOG 2024

designplan<sup>®</sup> 

**STRAL**

79 Trenton Avenue  
Frenchtown, NJ 08825

[www.designplan.com](http://www.designplan.com)

Tel: (908) 996-7710  
Fax: (908) 996-7042

# ROTO



Inox Natural



Inox Graphite



Inox Bronze



CRI>80

IP66

IK08



The spacer integrated with the lamp body makes the product compact. Made of stainless steel AISI 316L. Extra-clear black silk-screened tempered glass, 0.16 inches thick. Available in single and dual emission versions with one, two, or three LEDs to meet different design requirements. Optics include 21°, 45°, 65°, asymmetric, and street optics with color temperatures of 2700K, 3000K, and 4000K; the latter two optics are available only for single emission versions. Integrated power supply. Surface finish HCT available in three variants.




Emission



21°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power  
5W



45°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm


Power  
5W





65°

Color	2700K	3000K	4000K
	543 lm	550 lm	613 lm

Power  
5W



IP66 IK08 lm Orientable




Emission



21°

Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	


Power  
10W



45°

Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	


Power  
10W





65°

Color	2700K	3000K	4000K
1086 lm	1100 lm	1226 lm	

Power  
10W



IP66 IK08 lm Orientable




Emission



21°

Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	


Power  
15W



45°

Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	


Power  
15W



65°

Color	2700K	3000K	4000K
1629 lm	1650 lm	1839 lm	

Power  
15W



IP66 IK08 lm Orientable