

TECHNICAL CATALOG 2024

designplan[®] 

STRAL

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

SILL



Inox Natural



Inox Graphite



Inox Bronze

CRI>80

IP66


IK08



EN The spacer integrated with the lamp body makes the product compact. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 0.16 inches thick. Stainless steel screws with color matched to the finish. Mono and bi-emission versions with three LEDs for greater light output. 21°, 45° and 65° optics at 2700K, 3000K and 4000K. Integrated power supply. HTC surface finish available in three variants.



3.94"



3.94"

6.30"


Emission



21°

Color		
2700K	3000K	4000K
1629 lm	1650 lm	1839 lm


Power
15W



45°

Color		
2700K	3000K	4000K
1629 lm	1650 lm	1839 lm


Power
15W





65°

Color		
2700K	3000K	4000K
1629 lm	1650 lm	1839 lm

Power
15W



IP66 IK08 lm




Emission



21° + 21°

Color		
2700K	3000K	4000K
2x1629 lm	2x1650 lm	2x1839 lm


Power
2x15W



45° + 45°

Color		
2700K	3000K	4000K
2x1629 lm	2x1650 lm	2x1839 lm


Power
2x15W



65° + 65°

Color		
2700K	3000K	4000K
2x1629 lm	2x1650 lm	2x1839 lm

Power
2x15W



IP66 IK08 lm