EYE L 300

datasheet

EYE L 300 is a linear outdoor ceiling lamp that comes in recessed, surface-mounted, or projector versions. It offers high luminous efficiency and perfect beam control with 5 optics options: spot, medium, flood, elliptical and grazing.



SURFACE MOUNTED



PROJECTOR / FLOODLIGHT



RECESSED

Fixture Dimensions and Installation Options - *see page 2*

TECHNICAL DATA

Wattage	24W
Power Supply	Integral 120-277VAC
Dimming	On/Off (0-10V Remote Driver on request)
Construction	Body: Extruded Aluminum Lens: Extra Clear Glass Diffuser
CCT	2700K, 3000K (2200K, RGBW on request)
CRI	>90
Delivered Lumens	1741 lm (12°) 1783 lm (30°) 1657 lm (45°) 1896 lm (25°x 60°) 1718 lm (25° x 60° ß10°)
Efficacy	96.7 lm/W (12°) 99.1 lm/W (30°) 92.1 lm/W (45°) 105.3 lm/W (25°x 60°) 95.4 lm/W (25° x 60° ß10°)
Optics	12°, 30°, 45°, 25°x60°, 25°x60° ß10°
Finishes	5 Standard, See Below
Fixture Dimensions	12.5” l x 3.0” h x 1.9” w (surface mount version) 13.8” l x 4.3” h x 1.9” w (projector version) 13.0” l x 3.7” h x 4.3” w (recessed version)
Lumen Maintenance	L80, B15 >60,000hrs (Ta 40°C)
Color Consistency	3-Step MacAdam
IP Rating	IP67
Impact Resistance	IK10

ORDERING INFORMATION

Example: LNEYL3POSFHBEZU.US. Accessories ordered separately.

LNEYL3				**BEZ**		.	**US**
Model #	**Size**	**Optics**	**CCT**	**Power**	**Finish**		
LNEYL3	**POS** - Surface Mount **PR1** - Projector **ISO** - Recessed *NOTE: Recessed version only available in white finish*	**S** - 12° Spot **M** - 30° Medium **F** - 45° Flood **E** - 25° x 60° Elliptical **G** - 25° x 60° ß10° Grazing	**Y** - 2700K **H** - 3000K	**BEZ** - Integral	**G** - Black **H** - Gray **L** - Graphite **V** - Oxide **U** - White *Recessed version only available in white finish*		**US**

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2023 Designplan Lighting, Inc.


Published: November 6, 2026

P: 908-996-7710
F: 908-996-7042


EYE L 300


datasheet


FIXTURE DIMENSIONS




Ceiling version













Projector version






Recessed version






recessed installation



flush installation



protruding installation

ACCESSORIES - Included

Ceiling Version

1.6' (0.5 m) length cable -05RN-F
Single connection IP68

Projector Version

3.28' (1 m) length cable -05RN-F
Single connection IP68
Fixing kit short (3.0")

OPTIONAL

00KEYFGL.150_ - *Fixing kit medium (5.91")*
(available in different colors)
00KEYFGL.250_ - *Fixing kit long (9.84")*
(available in different colors)
Visor

COLOR OPTIONS
G - Black
H - Gray
L - Graphite
V - Oxide
U - White

Recessed Version

1.6 ft (0.5 m) length cable -05RN-F
Single connection IP68

OPTIONAL

00EY/FGL3.STD - *Housing box*

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com


79 Trenton Avenue, Frenchtown NJ 08825
© Copyright 2023 Designplan Lighting, Inc.
Published: November 6, 2026
P: 908-996-7710
F: 908-996-7042

PHOTOMETRIC DATA

Note: All photometric data is 3000K

12°


Maximum Candela = 10684.1



PHOTOMETRIC FILENAME : EYE-1 300 12° - EYL3XXXSHB10X.IES

30°


Maximum Candela = 4515.6



PHOTOMETRIC FILENAME : EYE-1 300 30° - EYL3XXXMHB10X.IES

25°x60°


Maximum Candela = 8516.4



PHOTOMETRIC FILENAME : EYE-1 300 25° X 60° - EYL3XXXEHB10X.IES

25°x60° ß10°

Maximum Candela = 4749.1



PHOTOMETRIC FILENAME : EYE-1 300 25° X 60° ß10° - EYL3XXXGHB10X.IES

Job Name/Date:

Fixture Type Designation:

sales@designplan.com
www.designplan.com

79 Trenton Avenue, Frenchtown NJ 08825

© Copyright 2023 Designplan Lighting, Inc.

Published: November 6, 2026

P: 908-996-7710
F: 908-996-7042