



Product

# FLEX

## About

Compact and sober, its reduced volume combined with the bracket that allows it to orient itself on the support to which it is applied, make it extremely versatile. From this concept comes FLEX, the double-axis swivel version of the standard FIXED.



79 Trenton Avenue  
Frenchtown, NJ 08825

[www.designplan.com](http://www.designplan.com)

Tel: (908) 996-7710  
Fax: (908) 996-7042



# M 01



Inox Natural



Inox Graphite



Inox Bronze



# M 02



Inox Natural



Inox Graphite



Inox Bronze



# M 03



Inox Natural



Inox Graphite










Inox Bronze





The spacer integrated with the lamp body makes the product compact. Adjustable bracket to allow movements in all directions. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 0.16" thick. Single emission versions with one, two or three LEDs for different design needs. 21°, 45° and 65° optics at 2700K, 3000K and 4000K. Integrated power supply. HCT surface finish available in three variants.






FLEX M01





Color			Emission
2700 K 543 lm	3000 K 550 lm	4000 K 613 lm	
Power 5W		Codes Technical details	 21°
			 45°
			 65°
IP66 IK08  Orientable			






FLEX M02



Color			Emission
2700 K 1087 lm	3000 K 1100 lm	4000 K 1227 lm	
Power 10W		Codes Technical details	 21°
			 45°
			 65°
IP66 IK08  Orientable			

FLEX M03



Color			Emission
2700 K 1630 lm	3000 K 1650 lm	4000 K 1840 lm	
Power 15W		Codes Technical details	 21°
			 45°
			 65°
IP66 IK08  Orientable			

