

datasheet

Kandovan is a recessed, wall mounted LED that is perfect for walkways, fence walls and stairways. It is available in 2 sizes, one with wide optics and the other with asymmetric optics, and 3 Hard Coat Treatment finishes. Kandovan H-130 is the 3W, 3.0" x 5.2" version with asymmetric wide optics.

TECHNICAL DATA

Wattage / Input	3W		
Power Supply	Remote 700mA, not included - See page 2		
Dimming	See Power Supplies		
Construction	Body/Frame: AISI 316L Stainless Steel Optical Reflector for Grazing Light in AISI 316L Stainless Steel		
ССТ	2700K, 3000K, 4000K		
CRI	>80		
Delivered Lumens	197 lm per beam (3000K)		
Efficacy	65.7 lm/W per beam (3000K)		
Optics	Wide		
BUG Rating	B0-U1-G0 (3000K)		
Lumen Maintenance	100,000 hrs L80, B10 (Ta 25°C)		
Hard Coat Finishes	Inox Natural, Inox Graphite, Inox Bronze		
Fixture Dimensions	5.24" h x 2.95" w (H-130)		
IP Rating	IP65		
Impact Resistance	IK08		
Warranty	10 Years Against Corrosion 5 Years on Electrical Components		

Hard Coating Treatment is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.


ORDERING INFORMATION

Example: SPT2022035B.US. Power Supplies / Accessories sold separately.

SPT20220				.US
Model No.	ССТ	Optics	Finishes	
SPT20220 (H-130)	2 - 2700K 3 - 3000K 4 - 4000K	5 - Wide (only on the H130 version)	N - Inox Natural G - Inox Graphite B - Inox Bronze	.US

Job Name/Date: Fixture Type Designation:

Fixture Dimensions



P: 908-996-7710 F: 908-996-7042

1 of 2