


Khori is an IP66-rated bollard made of stainless steel with 360° light emission that is perfect for lighting pathways and gardens. It is available in 2 versions, pole diameter of 1.6" or 2.8", and 4 different heights in each version, and 3 Hard Coat Treatment finishes. Khori D-40 is the 1.6" pole diameter version.



## TECHNICAL DATA

<b>Wattage / Input</b>	7W
<b>Power Supply</b>	Integral 120VAC
<b>Dimming</b>	On/Off Only
<b>Construction</b>	Body: AISI 316L Stainless Steel Lens: Transparent Polycarbonate
<b>CCT</b>	2700K, 3000K, 4000K
<b>BUG Rating</b>	B0-U1-G0 (3000K)
<b>CRI</b>	>85
<b>Delivered Lumens</b>	353 lm (3000K)
<b>Efficacy</b>	50.4 lm/W
<b>Optics</b>	360° (Rotosymmetrical)
<b>Lumen Maintenance</b>	100,000 hrs L80, B10 (Ta 25°C)
<b>Hard Coat Finishes</b>	Inox Natural, Inox Graphite, Inox Bronze
<b>Fixture Dimensions</b>	Head: Ø2.8" Ø1.6" Pole x 11.8", 19.7", 27.6" or 35.4" (D-40)
<b>IP Rating</b>	IP66
<b>Impact Resistance</b>	IK07
<b>Warranty</b>	10 Years Against Corrosion 5 Years on Electrical Components

Fixture Dimensions



**Hard Coating Treatment** is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.

## ORDERING INFORMATION


Example: SPT6074375B.US. Power Supplies / Accessories sold separately.

SPT6074		7			.US
Model No.	CCT	Optics	Height	Finishes	
SPT6074 (D-40)	2 - 2700K	7 - 360°	3 - 11.8"	N - Inox Natural G - Inox Graphite B - Inox Bronze	.US
	3 - 3000K		5 - 19.7"		
	4 - 4000K		7 - 27.6"		
			9 - 35.4"		


Job Name/Date:

Fixture Type Designation:

## ACCESSORIES




**PT68000**  
Flange with 4 Anchor Bolts  
for KHORI  
**(REQUIRED)**



## PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 114.2



PHOTOMETRIC FILENAME : KHORI D-40 30CM - PT6074373N.IES

Job Name/Date:

Fixture Type Designation: