

Kran is an IP66-rated bollard made of stainless steel, available in versions with 1, 2, or 3 LEDs in the head, and 2 heights for each style. It is available in 3 color temperatures, 5 optics options, and 3 Hard Coat Treatment finishes. Kran M-02 is the double LED version. Dark Sky compliant.

TECHNICAL DATA

| | |
|---------------------------|--|
| Wattage | 10W |
| Power Supply | Integral 120VAC |
| Dimming | On/Off Only |
| Construction | Body: AISI 316L Stainless Steel Lens: Flush Black Silk-screened Glass Extra-clear, Tempered, 0.16" Thick |
| CCT | 2700K, 3000K, 4000K |
| CRI | >80 |
| Delivered Lumens | 550 lm per beam (3000K) Dark Sky compliant |
| Efficacy | 110 lm/W per beam (3000K) |
| Optics | 21°, 45°, 65°, Asymmetric, Road |
| BUG Rating | B0-U1-G0 (21°, 45° - 3000K) B1-U1-G0 (65° - 3000K) |
| Lumen Maintenance | 100,000 hrs L80, B10 (Ta 25°C) |
| Hard Coat Finishes | Inox Natural, Inox Graphite, Inox Bronze |
| Fixture Dimensions | 23.6" or 35.4" height M-02 head: 7.24" l x 2.36" h |
| IP Rating | IP66 |
| Impact Resistance | IK08 |
| Warranty | 10 Years Against Corrosion 5 Years on Electrical Components |

Hard Coating Treatment is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.

ORDERING INFORMATION

Example: SPT6012366B.US. Accessories sold separately.



| | | | | | |
|------------------|-------------------------------------|---|------------------------|--|-----|
| SPT6012 | | | | | .US |
| Model No. | CCT | Optics | Height | Finishes | |
| SPT6012 (M-02) | 2 - 2700K 3 - 3000K 4 - 4000K | 2 - 21° 4 - 45° 6 - 65° 7 - Asymmetrical 8 - Road | 6 - 23.6" 9 - 35.4" | N - Inox Natural G - Inox Graphite B - Inox Bronze | .US |

Job Name/Date:

Fixture Type Designation:




Fixture Dimensions




FINISHES




ACCESSORIES



PT64010
Anchor Flange
4.13" w x 2.76" h
(REQUIRED)



2.36"
1.97"




PT64000
Anchor Bolts Kit
(Set of 4 Bolts)
6.30" w x 10.63" h x 3.94" l
(REQUIRED)


PHOTOMETRIC DATA

Note: All photometry is 3000K


21°



45°



65°



Job Name/Date:

Fixture Type Designation: