

datasheet

Kran is an IP66-rated bollard made of stainless steel, available in versions with 1, 2, or 3 LEDs in the head, and 2 heights for each style. It is available in 3 color temperatures, 5 optics options, and 3 Hard Coat Treatment finishes. Kran M-03 is the triple LED version. Dark Sky compliant for output below 80°.

TECHNICAL DATA

187.44	45)44 (14.00)			
Wattage	15W (M-03)			
Power Supply	Integral 120VAC			
Dimming	On/Off Only			
Construction	Body: AISI 316L Stainless Steel Lens: Flush Black Silk-screened Glass Extra-clear, Tempered, 0.16" Thick			
ССТ	2700K, 3000K, 4000K			
CRI	>85			
Delivered Lumens	550 lm per beam (3000K) Dark Sky compliant, output below 80°			
Efficacy	110 lm/W per beam (3000K)			
Optics	21°, 45°, 65°, Asymmetric, Road			
BUG Rating	B0-U1-G0 (21° - 3000K) B1-U1-G0 (45°, 65° - 3000K)			
Lumen Maintenance	100,000 hrs L80, B10 (Ta 25°C)			
Hard Coat Finishes	Inox Natural, Inox Graphite, Inox Bronze			
Fixture Dimensions	23.6" or 35.4" height M-03 head: 8.78" I x 2.36" h			
IP Rating	IP66			
Impact Resistance	IK08			
Warranty	10 Years Against Corrosion 5 Years on Electrical Components			

Hard Coating Treatment is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.

ORDERING INFORMATION

Example: SPT6013366B.US. Accessories sold separately.

SPT6013					.US		
Model No.	ССТ	Optics	Height	Finishes			
SPT6013 (M-03)	2 - 2700K	2 - 21°	6 - 23.6"	N - Inox Natural	.us		
	3 - 3000K	4 - 45°	9 - 35.4"	G - Inox Graphite			
	4 - 4000K	6 - 65°		B - Inox Bronze			
		7 - Asymmetrical					
		8 - Road					
Job Name/Date:	1	Fixture Type Designation:					

Fixture Type Designation:



Fixture Dimensions









P: 908-996-7710 F: 908-996-7042




datasheet





ACCESSORIES




PT64000 Flange with 4 Anchor Bolts for KRAN (REQUIRED)


PHOTOMETRIC DATA

Note: All photometry is 3000K






45°



65°



Job Name/Date:

Fixture Type Designation:

2 of 2