



Product

OLY

About

OLY has always been one of the reference products of the Stral collection. Over the years, the various light sources of the moment have followed one another inside it and today we present it in this way, with even more attention to detail, even more reliable and performing, to continue to safely illuminate the outdoors between facades and architectural spaces.

designplan® 

79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

STRAL

N 110



Inox Natural



Inox Graphite



Inox Bronze



N 180



Inox Natural



Inox Graphite



Inox Bronze



N 240



Inox Natural



Inox Graphite





Inox Bronze



Ring and lamp body in AISI 316L stainless steel, including the part embedded in the ground. 21°, 45° and 65° optics at 2700K, 3000K and 4000K and with GU10 lampholder for OLY N110. Stainless steel fixing screws with color matched to the finish. Installation in the ground and/or on the floor through raised casing. 0.31" thick extra-clear tempered glass. Inte-grated power supply. HCT surface finish available in three variants.

OLY N110



Color			Emission
2700 K 543 lm	3000 K 550 lm	4000 K 613 lm	
<hr/>			
Power 5 W		Codes Technical details	 21°
			 45°
			 65°

IP66



IP67

IK09

Accessories sold separately

GU10 220 V		Codes Technical details
---------------	--	----------------------------

OLY N180



Color			Emission	
2700 K	3000 K	4000 K		21°
1522 lm	1540 lm	1717 lm		45°
Power			Codes	
12 W		Technical details		
				65°

Color			Emission
2700 K	3000 K	4000 K	 21°
2174 lm	2200 lm	2453 lm	
<hr/>			 45°
Power		Codes	
18 W		Technical details	
			 65°



IP66

IP67

IK09

Accessories sold separately

OLY N240



Color			Emission	
2700 K	3000 K	4000 K		21°
2964 lm	3000 lm	3345 lm		45°
Power			Codes	
24 W		Technical details		
				65°

IP66

IP67

IK09

Accessories sold separately



