



Product

ROTO

About

A rotating version of FIXED that combines its reduced volume with a bracket with a joint that allows circular movements on the axis to which it is applied, making it extremely functional. From this concept comes ROTO, to give projects imagination and adaptability.



79 Trenton Avenue
Frenchtown, NJ 08825

www.designplan.com

Tel: (908) 996-7710
Fax: (908) 996-7042

M 01



Inox Natural



Inox Graphite



Inox Bronze



M 02



Inox Natural



Inox Graphite



Inox Bronze



M 03



Inox Natural



Inox Graphite










Inox Bronze




The spacer integrated with the lamp body makes the product compact. Bracket with joint for 360° rotation on one axis. Made of AISI 316L stainless steel. Flush black silk-screened glass extra-clear tempered, 0.16" thick. Single-emission version with one, two or three LEDs for different design needs. 21°, 45° and 65° optics at 2700K, 3000K and 4000K. Integrated power supply. HCT surface finish available in three variants.





ROTO M01





Color			Emission
2700 K 543 lm	3000 K 550 lm	4000 K 613 lm	
<div>Power 5W</div> <div></div> <div>Codes Technical details</div>			
			 21°
			 45°
			 65°
IP66		IK08	 Orientable





ROTO M02



Color			Emission
2700 K	3000 K	4000 K	
1087 lm	1100 lm	1227 lm	
Power 10W		Codes Technical details	 21°
			 45°
			 65°
IP66			IK08
Orientable			

ROTO M03



Color			Emission
2700 K	3000 K	4000 K	
1630 lm	1650 lm	1840 lm	
Power 15W		Codes Technical details	 21°
			 45°
			 65°
IP66			IK08
Orientable			

