

Kupolo Gloss

Kupolo Gloss is a fully configurable, handcrafted, circular, decorative dome pendant, made of high-grade acrylic, and available in multiple etch-designs and a choice of 3 dome colors. It is available in 4 diameters: 21.7", 29.6", 37.5" and 45.4", and static white or tunable white options. PROVIDED WITH INTEGRAL DALI2 DRIVER. REQUIRES REMOTE 48VDC non-dim DRIVER AND DALI CONTROLS PROVIDED BY OTHERS.



Fixture Dimensions - See Page 2

TECHNICAL DATA

Wattage	STATIC WHITE	TUNABLE WHITE
	88W - 21.7" (550 mm)	138W - 21.7" (550 mm)
	120W - 29.6" (750 mm)	181W - 29.6" (750 mm)
	152W - 37.5" (950 mm)	233W - 37.5" (950 mm)
	184W - 45.4" (1150 mm)	284W - 45.4" (1150 mm)
Power Supply	Remote 48VDC, not included. See page 2. Integral DALI2 drivers - Dali controls provided by others	
Construction	Dome: 0.31" High-grade Acrylic Ring: CNC Milled High-grade Aluminum Lens: 0.24" High-grade Satin Acrylic	
CCT	2700K, 3000K, 4000K, 5000K, 6500K Tunable White 2200-6500K	
CRI	80 (90 optional for 2700K, 3000K, 4000K)	
Delivered Lumens	6,389 lm (21.7" - 30K)	9,859 lm (21.7" - TW)
	8,711 lm (29.6" - 30K)	13,442 lm (29.6" - TW)
	11,037 lm (37.5" - 30K)	17,031 lm (37.5" - TW)
	13,355 lm (45.4" - 30K)	20,608 lm (45.4" - TW)
Efficacy	73 lm/W (3000K)	
Optics		
Dome, Ring Colors	3 Dome, 4 Ring, 6 Etch Designs - See Below	
Fixture Dimensions	9.9" x Ø21.7", 13.5" x Ø29.6" 17.0" x Ø37.5", 21.7" x Ø45.4"	
Lumen Maintenance	100,000 hrs L80, B10 (Ta 25°C)	
Color Consistency	3-Step MacAdam	

ORDERING INFORMATION


Example: ARKUP-4-1-T-V-O-S-C.US. Power Supplies ordered separately.

ARKUP	-		-	1	-		-	V	-		-		-		-		US
Model #	Diameter	CRI	CCT	Style	Dome Gloss	Ring Trim	Etch Design										
ARKUP	4 - 45.4"	1 - 80	2 - 2700K	V - Concave	T - Taupe	A - Alum	C - Circle	US									
	3 - 37.5"		3 - 3000K		B - Blue Gray	B - Black	L - Lines										
	2 - 29.6"		4 - 4000K		O - Orange	S - Silver	S - Shade										
	1 - 21.7"		5 - 5000K			G - Gold	R - Rose										
			6 - 6500K				M - Mikado										
			T - Tunable White				W - Wave										

Job Name/Date:

Fixture Type Designation:

FIXTURE DIMENSIONS



SUGGESTED POWER SUPPLIES

48VDC

Part Number	Description	Input/Output	# of Fixtures			
			Ø21.7"	Ø29.6"	Ø37.5"	Ø45.4"
PPLT00492	Non-Dim	120-277VAC to 48VDC, 187W, Class 2	1-1	1-1	—	—
PPLT00672	Non-Dim	120-277VAC to 48VDC, 240W, Class 2	1-2	1-2	1-1	1-1
PPLT00566	Non-Dim	120-277VAC to 48VDC, 600W, Class 2	1-5	1-4	1-3	1-2

For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:

DOME COLORS



Taupe

BlueGrey

Orange

RING COLORS




Alu Matt

Black Matt

Silver

Gold

ETCH DESIGNS



Circle

Lines

Shade

Rose


Mikado

Wave

Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA - Note all Photometry is 3000K



Job Name/Date:

Fixture Type Designation: