



car-go_1 130

FLOOR RECESSED





Wattage	2.5 W
Voltage	24VDC
Beam	
Drive over	 max 12 m/h max 4409 lbs

TECHNICAL SPECIFICATIONS

Source lamp	LED 2.5W
Total wattage	2.5W
Voltage	24VDC
Control	Power supply not included (other controls on request*)
Light color	3000K (other colors on request**)
Luminous flux	115 lm (285 lm***)
Luminous efficacy	45 lm/W
McADAM steps	3
Beam	diffuse
CRI	> 90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	IP67
IK rating	IK10

- * Control available on request
DALI - 0/10V - DMX - TRIAC
- ** Light color available on request
2200K • 2700K • RGBW
- *** Source flux



E (FC)		
H (ft)	fc (3000 K)	Ø (ft)
3.28'	3.3	11.45'
6.56'	0.8	22.90'
9.84'	0.4	34.38'
13.12'	0.2	45.83'
16.40'	0.1	57.28'

MATERIALS

<i>Body</i>	Extruded aluminum EN AW6026
<i>Diffuser</i>	Opal glass
<i>Finishing</i>	Glass

ORDER CODE

CG L 1 IPT D H B 7 Z U

INCLUDED ACCESSORIES

<i>Code</i>	<i>Description</i>
-	0.5 m (1.64') length cable -05RN-F
-	Single connection IP68



AVAILABLE ACCESSORIES

<i>Code</i>	<i>Description</i>
00CCL1.STD	Housing box
0404M019	Three-way connection box mini

car-go_1 300

FLOOR RECESSED




Wattage	12W
Voltage	24VDC
Beam	
Drive over	 max 12 m/h max 4409 lbs


TECHNICAL SPECIFICATIONS

Source lamp	LED 12W
Total wattage	12W
Voltage	24VDC
Control	Power supply not included (other controls on request*)
Light color	3000K (other colors on request**)
Luminous flux	510 lm (1340 lm***)
Luminous efficacy	43 lm/W
McADAM steps	3
Beam	diffuse
CRI	> 90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	IP67
IK rating	IK10

DIFFUSE



- * Control available on request
DALI - 0/10V - DMX - TRIAC
- ** Light color available on request
2200K • 2700K • RGBW
- *** Source flux



E (FC)

H (ft)	fc (3000K)	Ø (ft)
3.28'	15.70	10.53'
6.56'	3.90	21.06'
9.84'	1.77	31.56'
13.12'	1.02	42.09'
16.40'	0.65	52.62'

MATERIALS

<i>Body</i>	Extruded aluminum EN AW6026
<i>Diffuser</i>	Opal glass
<i>Finishing</i>	Glass

ORDER CODE

CG L 3 IPT DH B 7 Z U

INCLUDED ACCESSORIES

<i>Code</i>	<i>Description</i>
-	1 m (3.28") length cable -05RN-F
-	Single connection IP68



AVAILABLE ACCESSORIES

<i>Code</i>	<i>Description</i>
00CGL30.STD	Housing box
0404M019	Three-way connection box mini

car-go_1 600

FLOOR RECESSED





Wattage	24W
Voltage	24VDC
Beam	
Drive over	 max 12 m/h max 4409 lbs

TECHNICAL SPECIFICATIONS

Source lamp	LED 24W
Total wattage	24W
Voltage	24VDC
Control	Power supply not included (other controls on request*)
Light color	3000 K (other colors on request**)
Luminous flux	1020 lm (2680 lm***)
Luminous efficacy	43 lm/W
McADAM steps	3
Beam	diffuse
CRI	> 90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	IP67
IK rating	IK10

DIFFUSE

- * Control available on request
DALI 0/10V - DMX - TRIAC
- ** Light color available on request
2200K • 2700K • RGBW
- *** Source flux



E (FC)

H (ft)	fc (3000 K)	Ø (ft)
3.28'	31.4	10.53'
6.56'	7.9	21.06'
9.84'	3.5	31.56'
13.12'	2.0	42.09'
16.40'	1.3	52.62'

MATERIALS

<i>Body</i>	Extruded aluminum EN AW6026
<i>Diffuser</i>	Opal glass
<i>Finishing</i>	Glass

ORDER CODE

CG L 6 IPT DH B 7 Z U

INCLUDED ACCESSORIES

<i>Code</i>	<i>Description</i>
-	1 m (3.28') length cable -05RN-F
-	Single connection IP68

AVAILABLE ACCESSORIES

<i>Code</i>	<i>Description</i>
00CGL60.STD	Housing box
0404M019	Three-way connection box mini

car-go_1 900

FLOOR RECESSED





Wattage	34W
Voltage	24VDC
Beam	
Drive over	 max 12 m/h max 4409 lbs

TECHNICAL SPECIFICATIONS

Source lamp	LED 34W
Total wattage	34W
Voltage	24VDC
Control	Power supply not included (other controls on request*)
Light color	3000K (other colors on request**)
Luminous flux	1300 lm (3120 lm***)
Luminous efficacy	38 lm/W
McADAM steps	3
Beam	diffuse
CRI	> 90
Life time	L80-B15 > 60.000 h Ta 40°C
IP rating	IP67
IK rating	IK10

DIFFUSE

- * Control available on request
DALI - 0/10V - DMX - TRIAC
- ** Light color available on request
2200K • 2700K • RGBW
- *** Source flux



E (FC)

H (ft)	fc (3000K)	Ø (ft)
3.28'	40.0	10.53'
6.56'	10.0	21.06'
9.84'	4.5	31.56'
13.12'	2.5	42.09'
16.40'	1.6	52.62'

MATERIALS

<i>Body</i>	Extruded aluminum EN AW6026
<i>Diffuser</i>	Opal glass
<i>Finishing</i>	Glass

ORDER CODE

CG L 9 IPT DH B 7 Z U

INCLUDED ACCESSORIES

<i>Code</i>	<i>Description</i>
-	1 m (3.28') length cable -05RN-F
-	Single connection IP68

AVAILABLE ACCESSORIES

<i>Code</i>	<i>Description</i>
00CGL90.STD	Housing box
0404M019	Three-way connection box mini



