

PHOTOMETRIC MEASUREMENT REPORT N° FOG Lineare L.300

Photometric measurement date: 21/07/2022

Company: LANDA

Operator: /Roberto

Type of photometric measurement: C - Gamma

The measurements have been performed in the following laboratory ambient conditions:

Temperature: 23°C+/-2°C

Relative humidity: 50%U.R.+/-15%U.R.

Air turbulence: < 0.2 m/s

Stabilization time before measurement: 1 hour

Regulations applied: UNI-EN 13032-4

Electro Magnetic Compatibility (EMC): Shielded instrument

Luminaire name: FOG Lineare L.300

Eulumdat reference: FOG Lineare L.300

Size of luminaire (mm): 47 x 318 x 70

Size of luminous area (mm): 47 x 318

Number n of standard sets of lamps (optional): 1

Number of lamps: 1

Type of light source: Mid Power Led

Total luminous flux of the light source (lm): 1342

Output luminous flux of the lamp (lm): 510

Colour temperature (K): 2895

Colour rendering index: 93

Supply current (mA): 24V DC (@500mA)

Source power (W): 12

Power consumption included source power (W): 16

LED module efficacy (lm/W): 111.83

System light efficacy (lm/W): 83.88

Luminaire light efficacy (lm/W): 31.88

Light Output Ratio of luminaire (LOR): 100

Downward Flux Fraction (DFF): 100

Upward Flux Fraction (UFF): 0.00

Tilt during measurement (for street luminaires): 0