


# FOG L 300

## CEILING OR WALL (SURFACE OR RECESSED), PROJECTOR

FOG L is a linear, outdoor ceiling or wall fixture that comes in surface-mounted, projector or recessed versions, each in 4 lengths offering high resistance to atmospheric elements and longevity. FOG L 300 is the 13 foot length that comes as a surface-mounted projector, or wall/ceiling versions that are available in 5 standard finishes. It also comes in a recessed wall or ceiling version.



Fixture Dimensions - see page 2

### TECHNICAL DATA

<b>Wattage</b>	12W
<b>Power Supply</b>	Remote 24VDC - See page 3 for options
<b>Construction</b>	Body: Extruded Aluminum EN AW6060 Lens: Opal Glass
<b>CCT</b>	2700K, 3000K
<b>BUG Rating</b>	—
<b>CRI</b>	>90
<b>Delivered Lumens</b>	510 lm (3000K)
<b>Efficacy</b>	32 lm/W
<b>Optics</b>	Diffuse
<b>Finishes</b>	5 Standard, See Below
<b>Fixture Dimensions</b>	12.5" l x 3.0" h x 1.9" w (Surface Mounted) 13.8" l x 4.3" h x 1.9" w (Projector) 13.0" l x 3.7" h x 4.3" w (Recessed)
<b>Lumen Maintenance</b>	L80, B15 >60.000 h (Ta 40°C)
<b>Color Consistency</b>	3-Step MacAdam
<b>IP Rating</b>	IP67
<b>Impact Resistance</b>	IK10

### ORDERING INFORMATION

Example: LNFGL3POSDHB7ZU.US. Power Supplies ordered separately.


<b>LNFG</b>		<b>D</b>		<b>B7Z</b>		<b>US</b>
<b>Model #</b>	<b>Size</b>	<b>Optics</b>	<b>CCT</b>	<b>Power</b>	<b>Finish</b>	
LNFG	L3 POS - Ceiling / Wall L3 PR1 - Projector L3 ISO - Recessed <i>NOTE: Recessed version only available in white finish</i>	D - Diffuse	Y - 2700K H - 3000K	B7Z - Remote Driver	G - Black H - Gray L - Graphite U - White <i>(Recessed version only in white)</i> V - Oxide	US

Job Name/Date:


Fixture Type Designation:

### FIXTURE DIMENSIONS


#### Ceiling or Wall



#### Projector



#### Recessed



### ACCESSORIES - Included

#### CEILING / WALL LAMP

**05RN-F** - 1.64' (0.5 m) length cable  
Single connection IP68

#### PROJECTOR

**05RN-F** - 3.28' (1 m) length cable  
Single connection IP68  
Fixing kit short (2.95")

#### RECESSED

**05RN-F** - 1.64' (0.5 m) length cable  
Single connection IP68

*Also Available*


**00EY/FGL3.STD** - Housing box

**00KEYFGL.150\_** - Fixing kit medium (5.91")  
(available in fixture finishes - see page 1)

**00KEYFGL.250\_** - Fixing kit long (9.84")  
(available in fixture finishes - see page 1)


### FIXTURE DIMENSIONS (additional)

#### Front View - Surface Mount




### RECESSED INSTALLATION OPTIONS


recessed installation



flush installation



protruding installation



Job Name/Date:

Fixture Type Designation:

# FOG L 300

## CEILING OR WALL (SURFACE OR RECESSED), PROJECTOR

### SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00284</a>	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-6
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-6

### Suggested Lutron Compatible - 12W (FOG L 300)

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
<a href="#">PPLT00530</a>	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-6

### DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715


Part Number	Description	Input/Output	# of Fixtures 12W
<a href="#">PPLT00715</a>	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-6

For other power supply options consult factory.

### PHOTOMETRIC DATA

Note: All photometric data is 3000K

Maximum Candela = 169.3



PHOTOMETRIC FILENAME : FOG 1 300 - FGL3XXXDHB10X.IES

Job Name/Date:

Fixture Type Designation: