


C1-MINI-HC-VL

C1-mini-HC-VL is an LED spotlight for installation on magnetic track, suitable for showcase lighting in museum and retail settings. It is 180° rotatable, 90° swiveling with an attachment for mounting flange. It is available with a variety of optics, 5 color temperatures and 3 standard finishes.



The dimming sensor is located at the cable entry in the lamp base. See more page 2.

TECHNICAL DATA

| | |
|---------------------------|---|
| Wattage / Input | 1W, 2W (12VDC) |
| Power Supply | Remote - See Magnetic Track Sheet |
| Dimming | On Board with Dimming Pen (included) Uses Dimming Pen for Individual Dimming |
| Construction | Body: Anodized Aluminum |
| CCT | 2700K, 3000K, 3500K, 4000K, 5700K |
| CRI | >90 |
| Delivered Lumens | 60 lm (1W, 3000K, 30°) 110 lm (2W, 3000K, 30°) |
| Efficacy | 60 lm/W (1W, 3000K, 30°) 55 lm/W (2W, 3000K, 30°) |
| Optics | 8 Standard 15° Glass Lens – Aspherical w/ Light Diffusion Foil |
| Finishes | 3 Standard, See Below |
| Fixture Dimensions | Ø0.65" x 0.79" (head) 7.87" (standard pole) |
| Lumen Maintenance | L80, B10 >50,000hrs |
| IP Rating | IP20 |

NOTE: Track to be ordered separately



ORDERING INFORMATION

Example: C1-MINI-HC-VL-10-40-18-G. Accessories / Power Supplies ordered separately.

| C1-MINI-HC-VL | - | | - | | - | | - | | |
|---------------|------------|------------|--------------|--------------------|---------------------------|--|---|--|--|
| Model No. | Wattage | CCT | Optics | Finish | | | | | |
| C1-MINI-HC-VL | 10 - 1W | 27 - 2700K | 08 - 8° | B - Anodized Black | | | | | |
| | 20 - 2W | 30 - 3000K | 15 - 15° * | S - Silver | | | | | |
| | | 35 - 3500K | 18 - 18° | G - Gold | | | | | |
| | 57 - 5700K | 40 - 4000K | 26 - 26° | 30 - 30° | C - Custom RAL | | | | |
| | | 57 - 5700K | 45 - 45° | 45 - 45° | (consult factory for "C") | | | | |
| | | | 80 - 80° | 80 - 80° | | | | | |
| | | | 47 - 47°+25° | 47 - 47°+25° | | | | | |
| | | | 40 - 40°+10° | 40 - 40°+10° | | | | | |

* GLASS LENS – ASPHERICAL WITH LIGHT DIFFUSION FOIL, SEE ACCESSORIES PAGE

Fixture Dimensions



Job Name/Date:

Fixture Type Designation:

ACCESSORIES - OPTIONAL



Honeycomb Grid
A000601




Anti-Glare Tube
A300003 - __
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
RAL - custom RAL



Inclined Tube
A300146 - __
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)



Snoot
A300005 - __
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)
RAL - custom RAL



***15° Glass Lens - Aspherical**
with Light Diffusion Foil



Barn Door
A300007 - __
SI - silver
SW - black
RAL - custom RAL



Zoom Optic (9°-33°)
A300138 - __
SI - silver
SW - black
CH - champagne (min. 10)
HA - hard anodized (min. 10)
GO - gold (min. 10)

**See separate sheet
for Magnetic Track.
Consult factory for
Remote Power
Supply for Magnetic
Track.**

DIMMING

Place the dimming pen in the sensor area. As soon as the green feedback LED lights up at the cable entry, the sensor is activated and the spotlight is dimmed. The dimming process stops by removing the pen. When the dimming pen is attached again, the dimming direction is changed. Your set dimming is automatically saved after approx. 5 - 10 seconds. The dimming range is flicker-free adjustable from 100% to 10% in 256 steps. The spotlight is set to 100% at initial start-up.






Dimming Pen included

Job Name/Date:

Fixture Type Designation:

PHOTOMETRIC DATA

for light colour ~3,000 K | standard lens 30° | colour rendering index typ. 97, R9 > 90, R12 > 90 | colour variation ≤ 3 SDCM



Job Name/Date:

Fixture Type Designation: