CIVICO CEMENTO




datasheet

Civico Cemento is a handmade, cement, wall mounted luminaire which can be customized with a house or building number. It is available with a 2700K stripLED light source to illuminate the number.

c Usus Intertek



Fixture Dimensions



TECHNICAL DATA

Wattage / Input	9.6W per 3.28 ft (1 meter)
Power Supply	Remote 24VDC, not included - see page 2
Light Source	StripLED
Dimming	Dimmable Warm White
Construction	Body: Concrete
ССТ	2700K, 3000K
CRI	>90
Delivered Lumens	790 lm / 3.28 feet (1 m) (3000K)
Efficacy	82.29 lm/W
Optics	Narrow
Finishes	Concrete
Fixture Dimensions	11.02" l x 7.87" h
IP Rating	IP55

ORDERING INFORMATION

Example: RART.70.011.27.US. Power supplies sold separately.

RART.70.011		us
Model No.	ССТ	
RART.70.011	27 - 2700K 30 - 3000K	US

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

CIVICO CEMENTO



datasheet

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00149	Non-Dim	120VAC to 24VDC, 10W, Class 2, IP65	1-2
PPLT00632	0-10V Dimming (Dim to Off)	120-277VAC to 24VDC, 12W, Class 2	1-2
PPLT00155	Non-Dim	120VAC to 24VDC, 30W, Class 2	1-6
PPLT00709	ELV/TRIAC & 0-10V Dimming to 5% and OFF	120-277VAC to 24VDC, 96W, Class 2, DAMP	1-19
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-20

For other power supply options consult factory.

PHOTOMETRIC DATA

Coming Soon

Job Name/Date: Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2