


Civico Cemento is a handmade, cement, wall mounted luminaire which can be customized with a house or building number. It is available with a 2700K stripLED light source to illuminate the number.

## TECHNICAL DATA

<b>Wattage / Input</b>	9.6W per 3.28 ft (1 meter)
<b>Power Supply</b>	Remote 24VDC, not included - see page 2
<b>Light Source</b>	StripLED
<b>Dimming</b>	Dimmable Warm White
<b>Construction</b>	Body: Concrete
<b>CCT</b>	2700K, 3000K
<b>CRI</b>	>90
<b>Delivered Lumens</b>	790 lm / 3.28 feet (1 m) (3000K)
<b>Efficacy</b>	82.29 lm/W
<b>Optics</b>	Narrow
<b>Finishes</b>	Concrete
<b>Fixture Dimensions</b>	11.02" l x 7.87" h
<b>IP Rating</b>	IP55



Fixture Dimensions



Uses Remote Driver  
Does not require a J-Box

## ORDERING INFORMATION

Example: RART.70.011.27.US. Power supplies sold separately.

RART.70.011 . . US

Model No.	CCT	US
RART.70.011	27 - 2700K 30 - 3000K	US

Job Name/Date:

Fixture Type Designation:

## SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
<a href="#">PPLT00284</a>	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-20
<a href="#">PPLT00543</a>	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	3-20

## DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures 4W
<a href="#">PPLT00715</a>	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-19

*For other power supply options consult factory.*

## PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation: