## **CIVICO CEMENTO**




datasheet

Civico Cemento is a handmade, cement, wall mounted luminaire which can be customized with a house or building number. It is available with a 2700K stripLED light source to illuminate the number.

# Intertek



**Fixture Dimensions** 



#### **TECHNICAL DATA**

Wattage / Input	9.6W per 3.28 ft (1 meter)		
Power Supply	Remote 24VDC, not included - see page 2		
Dimming	Dimmable Warm White		
Construction	Body: Concrete Light Source: StripLED		
ССТ	2700K		
Delivered Lumens	900 lm/3.28 feet (1 meter)		
Efficacy	93.8 lm/W		
Optics			
Finishes	Concrete		
Fixture Dimensions	11.02" l x 7.87" h		
IP Rating	IP65		

#### **ORDERING INFORMATION**

Example: RART.70.011.US. Power supplies sold separately.

RART.70.011	.US
Model No.	
RART.70.011	.us

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

## **CIVICO CEMENTO**



datasheet

#### SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00149	Non-Dim	120VAC to 24VDC, 10W, Class 2, IP65	1-2
PPLT00632	0-10V Dimming (Dim to Off)	120-277VAC to 24VDC, 12W, Class 2	1-2
PPLT00155	Non-Dim	120VAC to 24VDC, 30W, Class 2	1-6
PPLT00599	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 96W, Class 2	1-19
PPLT00158	Non-Dim	120VAC to 24VDC, 100W, Class 2	1-20
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	1-20

For other power supply options consult factory.

### PHOTOMETRIC DATA

Coming Soon

Job Name/Date: Fixture Type Designation: