COLONNA



datasheet


Colonna is 3.28 foot rechargeable battery lamp made of steel with a warm white light. It comes in painted iron or painted bronze finish and is IP66-rated for outdoor use.

TECHNICAL DATA

Wattage / Input	3W (350mA)		
Power Supply	Remote, not included. See page 2.		
Battery Life	10 hours 7 hours at maximum brightness		
Light Source	Glass on demand		
Construction	Body: Steel		
ССТ	2700K, 3000K		
CRI	>80		
Delivered Lumens	470 lm (3000K)		
Efficacy	156.7 lm/W (3000K)		
Optics	Narrow		
Finishes	Iron Painted, Bronze Painted		
Fixture Dimensions	7.87" x 7.87" x H 39.37"		
IP Rating	IP66		



Fixture Dimensions



ORDERING INFORMATION

Example: R30.033.7.27.US. Power supplies sold separately.

R30.033].[US
Model No.	Finish		ССТ	
R30.033	7 - Iron Painted 12 - Bronze Painted		27 - 2700K 30 - 3000K	US

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042





datasheet

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00130	Non-Dim 120-277VAC to 350mA, 3W		1-1
PPLT00466-P	0-10V Dimming to 1.0%	0-10V Dimming to 1.0% 120-277VAC to 350mA, 10W, Class 2, DAMP	
PPLT00495	Phase Dim (120V only)	120VAC to 350mA, 25W, IP66	3-8
PPLT00263	Leading/Trailing Edge Dimming to 10% (120V only)	120-277VAC to 350mA, 32W, Class 2	3-5
PPLT00561-P	0-10V Dimming to 0.1% (4 Channels)	120-277VAC to 350mA, 100W, Class 2	1-6

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ OR 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	1-2
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ OR 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	2-4
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ OR 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	4-6

For other power supply options consult factory.

PHOTOMETRIC DATA

Coming Soon

Job Name/Date:

Fixture Type Designation:

P: 908-996-7710 F: 908-996-7042

2 of 2