

Fiaccola is an outdoor LED luminaire on a 55" or 63" pole, made of steel or brass, that is suitable for installation in the ground using the stem base of the pole. It comes in 2700K or 3000K with a painted iron, bronze painted or natural brass finish.



TECHNICAL DATA

Wattage / Input	1W
Power Supply	Remote 350mA, not included. See page 2.
Construction	Body: Steel or Brass Lens: Decorative Glass
CCT	2700K, 3000K
CRI	>80
Delivered Lumens	100 lm
Efficacy	100 lm/W
Optics	Narrow
Finishes	Body: Iron Painted, Bronze Painted, Natural Brass Details: Natural Brass, Burnished Brass
Fixture Dimensions	Ø0.39" x H 55.12" Ø0.39" x H 62.99"
IP Rating	IP66

Fixture Dimensions



ORDERING INFORMATION

Example: R70.084.7.ON.27.US. Power Supplies sold separately.

R70.084				US
Model No.	Body Finish	Detail Finish	CCT	
R70.084	7 - Iron painted 12 - Bronze Painted ON - Natural Brass	ON - Natural Brass ONB - Burnished Brass	27 - 2700K 30 - 3000K	US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

350mA

Part Number	Description	Input/Output	# of Fixtures
PPLT00211	Non-Dim	120VAC to 350mA, 10W, Class 2	4-8
PPLT00496	Phase Dim (120V only)	120VAC to 350mA, 12W, Class 2, DAMP	3-7
PPLT00465-P	0-10V Dimming to 1.0%	120-277VAC to 350mA, 20W, Class 2, DAMP	1-13
PPLT00263	Leading / Trailing Edge Dimming to 10% (120V only)	120-277VAC to 350mA, 32W, Class 2	8-11
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 350mA, 100W, Class 2	2-14

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00247	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 7W, Class 2	4-4
PPLT00516	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 13W, Class 2	6-9
PPLT00179	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 350mA, 19W, Class 2	12-13

*For other power supply options consult factory.**Job Name/Date:**Fixture Type Designation:*