# HOKU D-50

Hoku is an outdoor, adjustable LED on-grade or floodlight made of stainless steel that can be installed on the floor, wall, or ceiling. It consists of a cylinder with parallel lines creating a pattern on the surface, that rotates  $360^{\circ}$  in the housing base. It is available in 3 standard Hard Coat Treatment finishes. Hoku D-50 is the Ø4.7" x 4.7" version.

### **TECHNICAL DATA**

Wattage	5W LED or GU4 (Lamp by Others)	
Power Supply	Remote 12VDC not included, consult factory	
Dimming	Determined by Lamp	
Construction	Body: AISI 316L Stainless Steel	
ССТ	2700K, 3000K	
CRI	>80	
Delivered Lumens	550 lm (3000K)	
Efficacy	110 lm/W (3000K)	
Optics	6°, 15°, 25°, 38°, 10°x 35°, Wide	
Hard Coat Finishes	Inox Natural, Inox Graphite, Inox Bronze	
Fixture Dimensions	Ø4.7" x 4.7" (HOKU D-50)	
IP Rating	IP66	
Impact Resistance	IK08	
Warranty	10 Years Against Corrosion	
	5 Years on Electrical Components	

**Hard Coating Treatment** is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.

#### ORDERING INFORMATION


Example: SPT5025040B.US. Power Supplies ordered separately.

Model No.	Fini
SPT5025040 - GU4 Bulb by Others	N - I
SPT5025020 - LED 2700K	G -
SPT5025030 - LED 3000K	B - I

	.US
Finishes	
N - Inox Natural	.US
<b>G</b> - Inox Graphite	
<b>B</b> - Inox Bronze	



**Fixture Dimensions** 



#### **FINISHES**



Inox Natural



Inox Graphite



Inox Bronze

#### SUGGESTED POWER SUPPLIES 12VDC - Consult Factory

Job Name/Date:

Fixture Type Designation:

## designplan®