


OLY is a round, recessed, stainless steel LED uplight suitable for outdoor installation in the ground or floor for illuminating facades and architectural spaces. It is available in 3 sizes, with 4 color temperatures, 3 optic options, and 3 Hard Coat Treatment finishes. OLY 110 is the Ø4.3" 5W or 7W version.

TECHNICAL DATA

Wattage	5W, 7W
Power Supply	Integral 120VAC
Construction	Body: AISI 316L Stainless Steel Lens: 0.31" Extra-clear, Tempered Glass
CCT	2700K, 3000K, 4000K
CRI	>80
BUG Rating	B0-U3-G0 (3000K) B0-U4-G0 (3000K - 7W - 21°, 45°, 60°)
Delivered Lumens	550 lm (5W, 3000K) 750 lm (7W, 3000K)
Efficacy	110 lm/W (5W, 3000K) 107 lm/W (7W, 3000K)
Optics	6°, 21°, 45°, 65°, Wall Washer
Lumen Maintenance	100,000 hrs L80, B10 (Ta 25°C)
Hard Coat Finishes	Inox Natural, Inox Graphite, Inox Bronze
Fixture Dimensions	Ø4.33" x 5.12" (N110)
IP Rating	IP66, IP67
Impact Resistance	IK09
Warranty	10 Years Against Corrosion 5 Years on Electrical Components



Fixture Dimensions



Hard Coating Treatment is the surface treatment of all the products by Stral Lighting. It is not a skin of color, but instead is a process that allows for the color to be absorbed all the way through. If a product is scratched, the color beneath is the same as the color on the surface. It guarantees a high superficial resistance to corrosion and atmospheric agents, as well as making the products anti-fingerprint and anti-stain. Available in three finishes Inox Natural, Inox Graphite and Inox Bronze.

ORDERING INFORMATION

Example: **SPT1011036BHC.US**. Accessories ordered separately.

					.US
Model No.	CCT	Optics	Finish	Filter	
SPT10110 (5W)	2 - 2700K	1 - 6°	N - Inox Natural	None	.US
SPT10150 (7W)	3 - 3000K	2 - 21°	G - Inox Graphite	HC - Honeycomb	
	4 - 4000K	4 - 45°	B - Inox Bronze	HA - Asymmetric	
		6 - 65°		NOTE: Honeycomb and Asymmetric Filter NOT available on 6° or Wall Washer optics	
		7 - Wall Washer			

Job Name/Date:

Fixture Type Designation:

VERSIONS



Asymmetric Lens



Honeycomb Lens

FINISHES



Inox Natural




Inox Graphite




Inox Bronze

ACCESSORIES




PT52122
Casing
for ground recessing
9.84" x 6.30"




Ø9.84"


Ø6.30"




PT40001
Bottom Cap
Screwless
Ø8.66"



Ø8.66"



PT40002
Mortar Cap
With Screws
Ø4.33"



Ø4.33"

Job Name/Date:


Fixture Type Designation:

PHOTOMETRIC DATA

NOTE: All photometry is 3000K


5W - 21°

Maximum Candela = 1993.5




5W - 45°

Maximum Candela = 674.2




5W - 65°

Maximum Candela = 389.9




with Honeycomb Filter


Maximum Candela = 1955.1



Maximum Candela = 661.2




Maximum Candela = 382.4




7W - 21°

Maximum Candela = 2587.7




7W - 45°

Maximum Candela = 875.2



7W - 65°

Maximum Candela = 506.1



Job Name/Date:

Fixture Type Designation: